eurolite®

EUROLITE Audience Blinder 2xPAR-36 DMX sil

Audience blinder for 2 PAR 36 120V/650W lamps (with dimmer)

Art. No.: 42103411

GTIN: 4026397449501









The article is no longer in our assortment.

Description:

A real blind shell!

To trust someone blindly shows a distinctive naivety, doesn't it? In terms of our audience blinder it spoils nothing to say that this is indeed not the case, as it has numerous amenities which do vindicate absolute confidence. The most striking feature - beside its exceptionally quick and extremely bright light expansion - surely is its already installed dimmer, which does function manually via a dip switch. A clear advantage compared to many other Blinders, which have to have the dimmer attached as it is not integrated. The effect is designed for 4PAR-36 120V/650W lamps, and can be operated with two DMX-channels and mounted both on the ceiling as well as the traverse.

Features:

- Manual dimming via DIP switches
- Each lamp is individually connected to an internal lustre terminal, so that any lamp of your choice can easily be wired
- Extreme and lightning-fast light displays
- Robust version
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- With mounting bracket Package contents
- 1 x spotlight, 1 x user manual

Logistic

EAN / GTIN: 4026397449501 Weight: 2,75 kg Length: 0.40 m Width: 0.20 m Heigth: 0.22 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

	230 V AC, 50 Hz
Power supply:	
Power consumption:	Max. 1300 W
IP classification:	IP20
Protection class:	Protection class I
Suitable lamp:	120 V/650 W PAR-36 G-53 STC
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1,0 mm² H05SS-F
Cable length:	Approx. 0,8 m
Base:	Wires
Lamp type:	Halogen lamp
DMX channels:	1
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Construction:	PAR-36
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Metal
Dimensions:	Width: 40 cm
	Depth: 18 cm
	Height: 24 cm
Weight:	2,42 kg
Mounting bracket	
Diameter mounting holes:	3 x Ø12mm
Material:	Metal, 4 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting