eurolite®

EUROLITE Audience Blinder 2xPAR-36 DMX bk

High-quality stage version

Art. No.: 42103413 GTIN: 4026397449525









List price: 177.31 €

incl. 19% VAT.

Features:

- Extreme and lightning-fast light displays
- Each lamp is individually connected to an internal lustre terminal, so that any lamp of your choice can easily be wired
- Robust version
- Manual dimming via DIP switches
- Control via stand-alone; DMX
- Dimmable
- The device is cooled by passive convection cooling
- With mounting bracket
- Package contents
- 1 x spotlight, 1 x user manual

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 1300 W
IP classification:	IP20
Protection class:	Protection class I
Suitable lamp:	120 V/650 W PAR-36 G-53 STC
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1,0 mm² H05SS-F

Logistic

EAN / GTIN: 4026397449525 Weight: 2,70 kg Length: 0.40 m Width: 0.19 m Heigth: 0.26 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Cable length:	Approx. 0,8 m
Fuse:	F 8 A fuse replaceable
Base:	Wires
Lamp type:	Halogen lamp
Lamp specification:	Dimmable
DMX channels:	1
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Construction:	PAR-36
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Metal
Dimensions:	Width: 38,8 cm
	Depth: 17 cm
	Height: 24 cm
Weight:	2,43 kg
Mounting bracket	
Diameter mounting holes:	3 x Ø12mm
Material:	Metal, 4 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting