EUROLITE Audience Blinder,8xPAR-36,10mm LED,alu

Improved technology - higher performance!

Art. No.: 42103484

GTIN: 4026397263558

The article is no longer in our assortment.

Description:

Improved technology - higher performance! The LED Audience-blinder is a new broom that sweeps clean. Of course, it does not sweep, but therefor it shines in a real fascinating manner. Compared to traditional blinders with halogene lamps, the power consumption is very low. Maybe the LEDs are not able to shine 40 metres far, but with their long-life guarantee and their possibility to perform color changes, strobes or other effects, the advantages of the LED blinder must not be denied. You can really put your trust on it, disappointment excluded!

Logistic

EAN / GTIN: 4026397263558
Weight: 15,50 kg
Length: 0.90 m
Width: 0.55 m
Heigth: 0.25 m

Features:

- Functions in stand-alone mode or with DMX interface
- Sound-control via built-in microphone; sensitivity adjustable
- DMX address selectable
- 5, 8, 14, 26 DMX channel selectable for various applications
- 14 internal programs
- Programmable color change speed, strobe effect, and fading time
- 2 x 16 character LCD display
- RGB color mixing
- Master/Slave function
- Swivelable lamp rows
- Rugged housing and an appealing design
- Ideal for bands, stages or solo entertainers
- Perfect in public places, main halls, lounges
- Ready for connection with safety-plug
- Particularly bright illuminating power of the LEDs
- LED diameter: 10 mm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- Available in aluminum or black
- Available in 4-lamp or 8-lamp versions

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	90,00 W
Dimensions:	Width: 48 cm Depth: 13 cm Height: 81 cm
DMX channels:	26
LED number:	432
Beam angle:	20°
Dimensions (L x W x H):	810 x 480 x 130 mm
Weight:	13.5 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.