

## EUROLITE M-200 Mobile TwinTop Light Set

Compact, mobile lighting system



# The article is no longer in our assortment.

#### Features:

Compact, mobile lighting system

- Combines four LED spots and four Matrix effects
- The standard light system for every small band, solo entertainers and parties
- Set consisting of: 42109700 EUROLITE LED KLS-200 Compact lightset, 51918559 EUROLITE LED MAT-Bar 4x64 Matrix strip, 60004120 Speaker system stand alu, black, 59007081 EUROLITE STV-3529 Adapter long
- Details to the products:
- KLS-200 Compact lightset
- DMX LED spotlight set with 4 spots
- 108 x 10 mm LED per spot (36 x red, 36 x green, 36 x blue)
- Movable and tiltable spotlights
- Sound-control via built-in microhone with sensitivity control
- MAT-Bar 4x64 Matrix strip
- Space-saving solution
- Diverse mounting options; via mounting hole for example
- 256 LEDs
- You can find more information under the respective article
- Control via stand-alone; DMX

#### EUROLITE LED KLS-200 Compact-Light-Set

Bar with 4 spots with 108 LEDs (RGB) each and carrying bag

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit









Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 108 x 10 mm LED per spot (36 x red, 36 x green, 36 x blue)
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microhone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 (preset, sound control, freeze, blackout)
- DMX512 control via regular DMX controller (occupies 15 channels)
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included)
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 432 powerful LEDs 10 mm R/G/B<BR> spots controlled separately
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; foot switch (optional)
- Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW
- 2; EASY SHOW 3
- With a beam angle of 25°
- For further information about this product, please refer to the Data Sheet under "Downloads" Package contents
- 1 x spotlight, 1 x bag

#### EUROLITE LED MAT-Bar 4x64 Matrix bar

Flower effect bar with 256 LEDs (RGB)

- DMX512 control via regular DMX controller (occupies 7 channels)
- The colorful flower beams change their direction of movement at every bass beat in sound controlled mode
- Sound controlled via built-in microphone
- Microphone sensitivity adjustable via rotary control
- Auto mode, speed adjustable via DMX
- Internal programs
- Master/Slave function
- Control panel with 4 buttons and LED display
- Rugged compact housing
- Ready for connection with power cord and plug
- Including mounting bracket and mounting hole (36 mm) with fixation screw for installation on a
- truss system or stand, and carry bag
- Control via stand-alone; DMX
- Preprogrammed in Light'J

#### OMNITRONIC Speaker System Stand alu bk

High-quality speaker stand

- Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height

#### EUROLITE STV-3529 Adapter long

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot
- Package contents
- 1 x device, 1 x user manual, 2 x knurled screw

## **Technical specifications:**

| IP classification:   | IP20   |
|----------------------|--|
| Lamp type:           | LED lamp                                     |
| Control:             | Stand-alone; DMX                             |
| Housing color:       | Black  |
| Legal specifications |  |
| Special product:     | Not designed for household room illumination |
| Intended use:        | Show effect lighting                         |

#### EUROLITE LED KLS-200 Compact-Light-Set

| Power supply:           | 230 V AC, 50 Hz  |
|-------------------------|--|
| Power consumption:      | 55 W   |
| IP classification:      | IP20   |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Lamp type:              | LED lamp   |
| LED type:               | 432 x 10 mm R/G/B  |
| DMX channels:           | 15   |
| Cooling:                | Passive convection cooling   |
| Control:                | Stand-alone; DMX; foot switch (optional)   |
| Preprogrammed in:       | Light J; LED PC-Control 512; EASY SHOW 1;<br>Light Captain; EASY SHOW 2; EASY SHOW 3             |
| Beam angle:             | 25°  |
| Beam angle (1/2 peak):  | 25°  |
| Housing color:          | Black  |
| Weight:                 | 8,65 kg  |
| Bag                     |  |
| Dimensions:             | Width: 120 cm  |
|                         | Depth: 12 cm   |
|                         | Height: 38 cm  |
| DMX connection:         | 3-pin XLR  |
| TV spigot:              | D = 28 mm  |
| Dimensions (L x W x H): | 1110 x 55 x 295 mm   |
| Legal specifications    |  |
| Special product:        | Not designed for household room illumination   |
| Intended use:           | Show effect lighting   |
|                         |  |

#### EUROLITE LED MAT-Bar 4x64 Matrix bar

Power supply:

230 V AC, 50 Hz

| Power consumption:      | 40,00 W                                      |
|-------------------------|--|
| IP classification:      | IP20   |
| Lamp type:              | LED lamp                                     |
| Control:                | Stand-alone; DMX                             |
| Preprogrammed in:       | Light´J                                      |
| Beam angle (1/2 peak):  | 15°  |
| Housing color:          | Black  |
| Dimensions:             | Width: 80 cm                                 |
|                         | Depth: 9 cm                                  |
|                         | Height: 23 cm                                |
| Weight:                 | 6,48 kg                                      |
| DMX channels:           | 7  |
| DMX connection:         | 3-pin XLR                                    |
| Sound-control:          | via built-in microphone                      |
| LED type:               | 5 mm   |
| LED number:             | 256  |
| Beam angle:             | 15°  |
| Mounting hole:          | D = 36 mm                                    |
| Dimensions (L x W x H): | 800 x 90 x 230 mm                            |
| Legal specifications    |  |
| Special product:        | Not designed for household room illumination |
| Intended use:           | Show effect lighting                         |
|                         |  |

#### OMNITRONIC Speaker System Stand alu bk

| Maximum carrying capacity: | 30 kg                |
|----------------------------|----------------------|
| Height:                    | Maximum: 230 cm      |
|                            | Minimum: 140 cm      |
| Type (general stands):     | Speaker stand/manual |
| Material:                  | Aluminum             |
| Color:                     | Black                |
| Weight:                    | 3,45 kg              |
| Maximum load:              | 30 kg                |
| Maximum load (DIN15560):   | 18 kg                |
| Minimum height:            | 1.40 m               |
| Maximum height:            | 2.20 m               |

### EUROLITE STV-3529 Adapter long

| Maximum load BGV C1 (8-fold): | 50 kg                      |  |
|-------------------------------|----------------------------|--|
| Maximum load WLL (4-fold):    | 100 kg                     |  |
| Attachment system:            | TV spigot Ø 28mm<br>Ø 35mm |  |
| Type (general stands):        | Accessory                  |  |
| Material:                     | Steel, 6 mm, powder-coated |  |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Dimensions: | Width: 8,50 cm   |
|-------------|------------------|
|             | Depth: 5 cm      |
|             | Height: 19,50 cm |
| Weight:     | 1,50 kg          |
|             |                  |