


EUROLITE KLS-Kombo Pack 2

Compact, mobile lighting system

Art. No.: 42109542

GTIN:



The article is no longer in our assortment.

Features:

Logistic

Compact, mobile lighting system

- Combines four LED spots and four flower effects
- The standard light system for every small band, solo entertainers and parties
- Set consisting of: 42109700 EUROLITE LED KLS-200 Compact lightset, 51918571 EUROLITE LED QDF-Bar RGBW light set, 60004120 Speaker system stand alu, black, 59007081 EUROLITE STV-3529 Adapter long, 30220405 OMNITRONIC XLR cable 3pin 1m bk
- Details to the products:
- KLS-200 Compact lightset
- DMX LED spotlight set with 4 spots
- 108 x 10 mm LED per spot (36 x red, 36 x green, 36 x blue)
- Movable and tiltable spotlights
- Sound-control via built-in microphone with sensitivity control
- QDF-Bar RGBW light set:
- DMX LED spotlight set with 4 LED spots, crossbar and transport bag
- Equipped with 228 x 5 mm LED
- Pivotable and tiltable spotlights
- Ultra-light ideally suited for mobile use
- Black lacquered metal version
- You can find more information under the respective article

EUROLITE LED KLS-200 Compact-Light-Set

Bar with 4 spots with 108 LEDs (RGB) each and carrying bag

- Complete LED light set with four slimline LED spots

- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 108 x 10 mm LED per spot (36 x red, 36 x green, 36 x blue)
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 (preset, sound control, freeze, blackout)
- DMX512 control via regular DMX controller (occupies 15 channels)
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included)
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 432 powerful LEDs 10 mm R/G/B spots controlled separately
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; foot switch (optional)
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- With a beam angle of 25°
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x spotlight, 1 x bag

OMNITRONIC Speaker System Stand alu bk

High-quality speaker stand

- Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height

EUROLITE STV-3529 Adapter long

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot

Package contents

- 1 x device, 1 x user manual, 2 x knurled screw

EUROLITE LED QDF-Bar RGBW light set

DMX LED spotlight set with 4 LED spotlights, crossbar and transport bag

- Complete LED light set consisting of 4 LED spots and a crossbar with an integrated DMX control unit and mounting hole (36 mm) with fixation screw for installation on a truss system or stand
- Pivotable and tiltable spotlights
- Each spot can be individually controlled via DMX
- DMX-512 control via regular DMX-controller (occupies 6 channels)
- Sound-control via built-in microphone with sensitivity control
- Strobe effect
- Auto mode
- Internal programs
- Master/Slave function
- Addressing and setting via control panel with 4-digit LED display and three operating buttons
- Additional controlling possibility via the EUROLITE RC-2 remote control (not included in the delivery)

- Equipped with 228 x 5 mm LEDs
- Ultra-light ideally suited for mobile use
- Suited for installation on a speaker stand (not included)
- Comes pre-assembled with a practical transport bag
- Black lacquered metal version
- Ready for connection with IEC power cord and safety plug
- Preprogrammed in Light´J

OMNITRONIC IEC Extension 3x0.75 1m**Package contents**

- 1 x power cord

Technical specifications:

Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED KLS-200 Compact-Light-Set

Power supply:	230 V AC, 50 Hz
Power consumption:	55 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	432 x 10 mm R/G/B
DMX channels:	15
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; foot switch (optional)
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	25°
Beam angle (1/2 peak):	25°
Housing color:	Black
Weight:	8,65 kg
Bag	
Dimensions:	Width: 120 cm Depth: 12 cm Height: 38 cm
DMX connection:	3-pin XLR
TV spigot:	D = 28 mm
Dimensions (L x W x H):	1110 x 55 x 295 mm
Legal specifications	
Special product:	Not designed for household room illumination

Intended use:	Show effect lighting
---------------	----------------------

OMNITRONIC Speaker System Stand alu bk

Maximum carrying capacity:	30 kg
Height:	Maximum: 230 cm Minimum: 140 cm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Weight:	3,45 kg
Maximum load:	30 kg
Maximum load (DIN15560):	18 kg
Minimum height:	1.40 m
Maximum height:	2.20 m

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold):	50 kg
Maximum load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm
Type (general stands):	Accessory
Material:	Steel, 6 mm, powder-coated
Dimensions:	Width: 8,50 cm Depth: 5 cm Height: 19,50 cm
Weight:	1,50 kg

EUROLITE LED QDF-Bar RGBW light set

Power supply:	230 V AC, 50 Hz
Power consumption:	50,00 W
Preprogrammed in:	Light´J
Dimensions:	Width: 86 cm Depth: 21 cm Height: 26 cm
Weight:	6 kg
DMX channels:	6
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	5 mm
LED number:	228
Beam angle:	23°
Mounting hole:	D = 36 mm

Dimensions (L x W x H):	860 x 210 x 260 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC XLR Cable 3-pin 1m bk

Cable construction:	2 x 0,22 mm ² microphone cable
Cable length:	1 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Dimensions:	Diameter: Ø 0,60 cm
Weight:	0,10 kg
Plug (male)	
Material:	Metal

OMNITRONIC IEC Extension 3x0.75 1m bk

Cable construction:	3 x 0,75 mm ² power cable
Cable length:	1 m
Plug A:	1 x IEC (M)
Plug B:	1 x IEC (F)
Color:	Black
Weight:	0,11 kg