



EUROLITE KLS-Kombo Pack 9

Universal mobile light set

Art. No.: 42109549

GTIN:



The article is no longer in our assortment.

Features:

Logistic

Universal mobile light set

- Combines six LED spots
- The standard light system for every small band, solo entertainers and parties
- Set consisting of: 42109890 EUROLITE LED KLS-2001 Compact lightset, 2 x 51915380 EUROLITE LED SLS-5 QCL 5x5W Floor, 60004120 Speaker system stand alu, black, 59007081 EUROLITE STV-3529 Adapter long
- Details to the products:
- KLS-2001 Compact lightset
- Complete LED light set with 4 spots
- Compact and easy to transport
- 7 quadcolor LEDs (QCL) per spot (3 x RGBA and 4 x RGBW)
- 4 IEC outputs for power supply of further devices
- SLS-5 QCL 5x5W Floor
- Equipped with 4in1 quadcolor LEDs for homogeneous light output in the colors red, green, blue and white
- For hanging or standing
- Flat housing form requires minimal space when rigging
- You can find more information under the respective article

EUROLITE LED KLS-2001 Compact light set

DMX LED spotlight set with 28 x 4in1 LED for mobile use

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit

- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- 7 quadcolor LEDs (QCL) per spot (3 x RGBA and 4 x RGBW)
- Comes pre-assembled with practical transport bag
- Through the close chip placement of the multichip technology, an exquisite color mix even with short distances to the illuminated surface is provided
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- DMX512 control via regular DMX controller (occupies 23 channels)
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included) or truss
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and PowerCon input
- 4 IEC outputs for power supply of further devices
- 28 powerful LEDs
- Preprogrammed in EASY SHOW 1; Light Captain
- For further information about this product, please refer to the Data Sheet under "Downloads"

OMNITRONIC Speaker System Stand alu bk

High-quality speaker stand

- Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height

EUROLITE STV-3529 Adapter long

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot

Package contents

- 1 x device, 1 x user manual, 2 x knurled screw

EUROLITE LED SLS-5 QCL 5x5W Floor

Slimline LED spot with 5 x 5 W 4in1 LED

- Equipped with 4in1 quadcolor LEDs for homogeneous light output in the colors red, green, blue and white
- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Comfortable addressing and setting via control panel with LED display
- Functions: Static colors, RGBW color blend, internal programs, dimmer, strobe, sound-control, sensitivity
- Further display settings: display on or off, display inverted, default settings
- Operable in stand-alone mode or via DMX
- Master/Slave for parallel operation of several devices
- DMX512 control via regular DMX-controller
- Number of DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Ready for connection with power cord and safety plug
- Feed-through output allows to power up to 8 devices
- Switch-mode power supply for operation between 100 and 240 volts
- Control via Sound to light via Microphone
- Preprogrammed in Light´J; Light Captain

OMNITRONIC XLR cable 3pin 0.5m bk

Audio cable with 3-pin XLR connectors<p class='attributgroup'>Package contents

- 1 x xLR cable

Technical specifications:

Weight:	25,01 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED KLS-2001 Compact light set

Power supply:	230 V AC, 50 Hz
Power consumption:	185,00 W
LED:	28
Preprogrammed in:	EASY SHOW 1; Light Captain
Dimensions:	Width: 1,2 m Depth: 6 cm Height: 31 cm
DMX channels:	23
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	8 W QCL
Number of LEDs:	28
Beam angle:	22°
TV spigot:	D = 28 mm
Dimensions (L x W x H):	1200 x 60 x 310 mm
Weight:	11 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC Speaker System Stand alu bk

Maximum carrying capacity:	30 kg
Height:	Maximum: 230 cm Minimum: 140 cm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Weight:	3,45 kg

Maximum load:	30 kg
Maximum load (DIN15560):	18 kg
Minimum height:	1.40 m
Maximum height:	2.20 m

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold):	50 kg
Max. load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm
Type (general stands):	Accessory
Material:	Steel, 6 mm, powder-coated
Dimensions:	Width: 8,50 cm Depth: 5 cm Height: 19,50 cm
Weight:	1,50 kg

EUROLITE LED SLS-5 QCL 5x5W Floor

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	24 W
IP classification:	IP20
DMX channels:	4
Control:	Sound to light via Microphone
Preprogrammed in:	Light´J; Light Captain
Beam angle (1/2 peak):	40°
Dimensions:	Width: 23 cm Depth: 11 cm Height: 27 cm
Weight:	2,95 kg
DMX channels:	4/6/7
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	5 W QCL
LED number:	5
Beam angle:	40°
Ventilation fan:	No
Dimensions (W x D x H):	230 x 110 x 270 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC XLR cable 3pin 0.5m bk

Cable construction:	Audio cable
Cable length:	0,5 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	80 g