

EUROLITE KLS-Kombo Pack 13

High performance mobile lighting system

Art. No.: 42109553

GTIN:



The article is no longer in our assortment.

Features:

High performance mobile lighting system

- Combines four LED spots and a flower bar
- The standard light system for every small band, solo entertainers and parties
- Set consisting of: 42109851 EUROLITE LED KLS-801 Compact lightset, 51918579 EUROLITE LED FE-Bar RGBAW light set, 60004120 Speaker system stand alu, black, 59007081 EUROLITE STV-3529 Adapter long
- Details to the products:
- KLS-801 Compact lightset
- Complete LED light set with 4 spots
- Compact and easy to transport
- 28 TCL LEDs
- 4 IEC outputs for power supply of further devices
- LED FE-Bar RGBAW light set
- Equipped with 20 x 1 W LED in red, green, blue, amber and white
- The colorful flower beams change their direction of movement at every bass beat in sound controlled mode
- Internal programs
- Master/Slave function
- You can find more information under the respective article

Logistic

EUROLITE LED KLS-801 Compact Light Set

Bar with 4 spots with 7 x 3 W 3in1 LED (RGB) each and carrying bag

- Complete LED light set with four slimline LED spots

- Crossbar with integrated DMX control unit
 - Installation via TV pin for tripods with 28 mm interior diameter
 - Ultra-light ideally suited for mobile use
 - Comes pre-assembled with practical transport bag
 - 7 TCL LEDs per spot
 - Through the close chip placement of the multichip technology, an exquisite color mix even with short distances to the illuminated surface is provided
 - Movable and tiltable spotlights
 - DMX-controlled operation or stand-alone operation with processor-controlled color change
 - Master/Slave operation
 - Sound-control via built-in microphone with sensitivity control
 - Convenient control possible via optional 4-pedal foot pedal FP-1 or IR remote control
 - Optimized for control with the optional control panel DMX LED Operator 4
 - Via DMX, each spot can be individually controlled
 - DMX functions: dimmer, automatic mode, music control, strobe effect
 - Addressing and setting via control panel with 4-digit LED display
 - Suited for installation on a lighting stand (not included) or truss
 - Black lacquered metal version
 - Ideal for bands, stages or solo entertainers
 - Ready for connection with power cord and safety plug
 - 4 IEC outputs for power supply of further devices
 - 7 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
 spots controlled separately
 - Control via stand-alone; DMX; Foot switch (optional); Sound to light via Microphone
 - Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
 - With a beam angle of 30°
 - TV spigot
 - For further information about this product, please refer to the Data Sheet under "Downloads"
- Package contents**
- 1 x spotlight, 1 x bag

OMNITRONIC Speaker System Stand alu bk

High-quality speaker stand

- Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height

EUROLITE STV-3529 Adapter long

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot

Package contents

- 1 x device, 1 x user manual, 2 x knurled screw

EUROLITE LED FE-Bar RGBAW light set

RGBAW flower effect bar with 1 W LEDs

- Equipped with 20 x 1 W LED in red, green, blue, amber and white
- DMX512 control via regular DMX controller (occupies 8 channels)
- The colorful flower beams change their direction of movement at every bass beat in sound controlled mode
- Sound controlled via built-in microphone
- Microphone sensitivity adjustable via rotary control
- Internal programs
- Master/Slave function
- Control panel with 3 buttons and LED display
- Rugged compact housing
- Ready for connection via enclosed IEC power cord with safety plug

- Mounting bracket and mounting hole (36 mm) with fixation screw for installation on a truss system or stand
- Preprogrammed in Light´J

OMNITRONIC XLR cable 3pin 0.5m bk

Audio cable with 3-pin XLR connectors<p class='attributgroup'>Package contents

- 1 x xLR cable

Technical specifications:

Weight:	22,48 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED KLS-801 Compact Light Set

Power supply:	230 V AC, 50 Hz
Power consumption:	90,00 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	4 x IEC connector (F) mounting version fused 1 x IEC connector (F) mounting version Bypass
Lamp type:	LED lamp
LED:	7 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
DMX channels:	15
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; Foot switch (optional); Sound to light via Microphone
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	30°
Beam angle (1/2 peak):	30°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm
Weight:	11,75 kg
Spotlight	
Dimensions:	Width: 1,2 m Depth: 6,5 cm Height: 31,5 cm
Bag	
Dimensions:	Width: 1,25 m

Depth: 12 cm

Height: 38 cm

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

OMNITRONIC Speaker System Stand alu bk

Maximum carrying capacity: 30 kg

Height: Maximum: 230 cm
Minimum: 140 cm

Type (general stands): Speaker stand/manual

Material: Aluminum

Color: Black

Weight: 3,45 kg

Maximum load: 30 kg

Maximum load (DIN15560): 18 kg

Minimum height: 1.40 m

Maximum height: 2.20 m

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold): 50 kg

Max. load WLL (4-fold): 100 kg

Attachment system: TV spigot Ø 28mm
Ø 35mm

Type (general stands): Accessory

Material: Steel, 6 mm, powder-coated

Dimensions: Width: 8,50 cm
Depth: 5 cm
Height: 19,50 cm

Weight: 1,50 kg

EUROLITE LED FE-Bar RGBAW light set

Power supply: 230 V AC, 50 Hz

Power consumption: 50,00 W

Preprogrammed in: Light´J

Dimensions: Width: 80 cm
Depth: 20 cm
Height: 19 cm

Weight: 5,70 kg

DMX channels: 8

DMX connection: 3-pin XLR

Sound-control: via built-in microphone

LED type: 1 W

LED number:	20
Beam angle:	40°
Mounting hole:	D = 36 mm
Dimensions (L x W x H):	800 x 200 x 190 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC XLR cable 3pin 0.5m bk

Cable construction:	Audio cable
Cable length:	0,5 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	80 g