

EUROLITE LED KLS-120 Compact Light Set

Compact Light Set with 4 RGBW Spots

Art. No.: 42109606

GTIN: 4026397677812



List price: 224.91 €

incl. 19% VAT.

Features:

- Crossbar with integrated DMX control unit and stand sleeve
 - Compact lightweight
 - For application areas such as: Wedding/gala/events; party room; mobile use; mobile djs / entertainer
 - 12 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
4 spots controlled separately
 - Silent operation
 - Color blend stepless; color change adjustable; colors preset; Dimmer electronic
 - Strobe effect
 - Flicker-free
 - Control via stand-alone; DMX; IR remote control; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Mains input and output for power linking up to 8 units
 - With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
 - Preprogrammed in EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief
 - Application possibility: Standing; on stand
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x bag

Logistic

EAN / GTIN: 4026397677812

Weight: 4,25 kg

Length: 0.64 m

Width: 0.30 m

Height: 0.17 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	30 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	4; 7; 16; 19
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief
Projection:	Flicker-free
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	34°
Housing color:	Black
Attachment system:	Ø 35mm Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 61,6 cm Depth: 10,0 cm Height: 22,6 cm
Weight:	3,70 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting