

EUROLITE LED KLS-120 FX Compact Light Set

DMX lighting effect bar with 2 rotating LED derbies and 2 LED spotlights

Art. No.: 42109607

GTIN: 4026397680751



List price: 255.85 €

incl. 19% VAT.

Features:

- Crossbar with integrated DMX control unit and stand sleeve
 - Compact lightweight
 - 2 rotating derbies for mirror ball effects
 - Silent operation
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
 - Direct color selection for 15 preset colors
 - 3 integrated show programs
 - Strobe effect
 - Flicker-free
 - Control via DMX; IR remote control; stand-alone; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3; Light´J
 - Mains input and output for power linking up to 8 units
 - 6 rubber feet
 - For application areas such as: Wedding/gala/events; Party room; mobile use; mobile djs / entertainer
 - Application possibility: Standing; on stand
- spotlight**
- 3 powerful LEDs 8 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
spots controlled separately
- light effect**
- 4 powerful LEDs 3 W high-power R/G/B/W
LEDs controlled separately
- Package contents**
- 2 x light effect, 1 x power cord, 1 x remote control, 1 x battery, 1 x bag, 1 x user manual

Logistic

EAN / GTIN: 4026397680751
Weight: 5,40 kg
Length: 0.66 m
Width: 0.17 m
Height: 0.36 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A Fuse replaceable
Lamp type:	LED lamp
DMX channels:	2; 9; 21
DMX input:	3-pin XLR (F) mounting version
DMX output:	3-pin XLR (M) mounting version
Cooling:	Passive convection cooling
Control:	DMX; IR remote control; stand-alone; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
Projection:	Flicker-free
Beam angle:	18°
Beam angle (1/2 peak):	Wash effect 18° Multi beam effect 90° multicolor
Housing color:	Black
Display type:	4 digit 7-segment LED display
Transport aid:	6 x rubber feet
Dimensions:	Width: 62,5 cm Depth: 15,5 cm Height: 22,4 cm
Weight:	4,70 kg
Noise classification:	Class 0 (no noise at all)
Power cord	
Cable construction:	H05VV-F
Cable length:	Approx. 1,2 m
Spotlight	
LED:	3 x 8 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Light effect	
LED:	4 x 3 W high-power R/G/B/W
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting