

EUROLITE LED KLS-170 Compact Light Set

Bar with 4 RGB spots, cold white + UV strobe LEDs, foot switch and carrying bag

Art. No.: 42109620

GTIN: 4026397582611



List price: 343.91 €

incl. 19% VAT.

Features:

- 2-in-1 DMX light set with four slimline LED spots and strobe LEDs in white and UV
- Ultra-light, ideally suited for mobile use
- Crossbar with integrated DMX control unit and stand sleeve
- Comes pre-assembled with practical transport bag
- 4 spots with 3 high-power RGB LEDs (3in1) each
- Mains input and output for power linking up to 8 units
- 4 powerful LEDs 2 W high-power 2in1 BCL CW/UV (homogenous color mix)
- 3 powerful LEDs 9 W high-power 3in1 TCL RGB (homogenous color mix)
- 31 integrated Showprograms
- Can be operated in 3; 6; 16; 25 CH mode
- The device is cooled by passive convection
- Controlling by stand-alone; DMX; Wireless footswitch; IR remote control; Sound to light via Microphone; Master/slave function; Sound to light
- Preprogrammed in EASY SHOW; Light´J; LED PC-Control 512; Light Captain
- With a beam angle of 13°
- With Mounting bracket

Logistic

EAN / GTIN: 4026397582611

Weight: 7,80 kg

Length: 1.07 m

Width: 0.29 m

Height: 0.16 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 90 W

IP classification: IP20

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	Strobe effect 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix) Spot 3 x 9 W high-power 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 30 Hz
DMX channels:	3; 6; 16; 25
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection
Control:	Stand-alone; DMX; Wireless footswitch; IR remote control; Sound to light via Microphone; Master/slave function; EASY SHOW; Light J; LED PC-Control 512; Light Captain; Sound to light
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	25°
Housing color:	Black
Attachment system:	2x Mounting bracket
Dimensions:	Width: 1,03 m Depth: 55 cm Height: 24 cm
Weight:	6,25 kg
Noise classification:	Class 0 (no noise at all)
Foot control	
Battery:	1 x 9.0 V E block 6F22 zinc carbon (provided)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting