

## EUROLITE LED KLS-180 Compact Light Set

Bar with 4 RGBW spots and 4 white strobe LEDs, with QuickDMX connector (XLR)

Art. No.: 42109630

GTIN: 4026397599046



**List price: 296.31 €**

incl. 19% VAT.

### Features:

- Crossbar with integrated DMX control unit and stand sleeve
- Ultra-light, ideally suited for mobile use
- Ideal for bands, mobile DJs and stages
- Suited for installation on a speaker stand (not included) or truss
- Comes pre-assembled with practical transport bag
- Movable and tiltable spotlights
- Each spot can be individually controlled via DMX
- Supports QuickDMX - the wireless DMX system from Eurolite
- Built-in phantom-powered socket for QuickDMX receivers (optional)
- Stepless color blend, color change, preset colors, dimmer and strobe effect
- Mains input and output for power linking up to 8 units
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- 4 powerful LEDs 1 W high-power cold white (CW)
- Can be operated in 3; 4; 8; 21 CH mode
- The device is cooled by passive convection
- Controlling by stand-alone; DMX; IR remote control; Sound to light via Microphone; QuickDMX via 5-pin XLR (M) mounting version (optional)
- Preprogrammed in EASY SHOW; LED PC-Control 512; Light Captain
- Flicker-free projection
- With a beam angle of 9°
- Monochrome 4 digits 7-segment LED display for easy controlling

### Logistic

EAN / GTIN: 4026397599046

Weight: 5,50 kg

Length: 0.66 m

Width: 0.19 m

Height: 0.29 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1,1 m
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	Spot 4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) Strobe effect 4 x 1 W high-power cold white (CW)
DMX channels:	3; 4; 8; 21
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); EASY SHOW; LED PC-Control 512; Light Captain
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	18°
Housing color:	Black
Display type:	Monochrome 4 digits 7-segment LED display
Dimensions:	Width: 60,5 cm Depth: 14 cm Height: 23 cm
Weight:	4,85 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting