

## EUROLITE LED KLS-180/6 Compact Light Set

Bar with 6 RGBW spots and 6 white strobe LEDs

Art. No.: 42109632

GTIN: 4026397690408



**List price: 427.21 €**

incl. 19% VAT.

### Features:

- Crossbar with integrated DMX control unit and stand sleeve
- Ultra-light, ideally suited for mobile use
- Suited for installation on a speaker stand (not included) or truss
- Comes pre-assembled with practical transport bag
- 6 spots with 4 powerful 8 W LEDs provide for an exquisite RGBW color mix
- Movable and tiltable spotlights
- Each spot can be individually controlled via DMX
- Built-in phantom-powered socket for QuickDMX receivers (optional)
- Stepless color blend, color change, preset colors, dimmer and strobe effect
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- 6 powerful LEDs 1 W high-power cold white (CW)
- Can be operated in 3; 4; 6; 8; 9; 11; 21; 24; 29 CH mode
- The device is cooled by passive convection
- Controlling by IR remote control; stand-alone; Sound to light via Microphone; DMX; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in EASY SHOW; Light Captain
- Flicker-free projection
- With a beam angle of 9°
- 4 digits 7-segment LED display for easy controlling

### Logistic

EAN / GTIN: 4026397690408

Weight: 7,60 kg

Length: 0.96 m

Width: 0.20 m

Height: 0.30 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	90 W
IP classification:	IP20
Protection class:	Class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	2 x IEC connector (F) mounting version
Fuse:	T 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	Spot 4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) Strobe effect 6 x 1 W high-power cold white (CW)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 6; 8; 9; 11; 21; 24; 29
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection
Control:	IR remote control; stand-alone; Sound to light via Microphone; DMX; Master/slave function; EASY SHOW; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Light Captain
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	18
Housing color:	Black
Display type:	4 digits 7-segment LED display
Dimensions:	Width: 92,6 cm Depth: 14,6 cm Height: 26,7 cm
Weight:	6,00 kg
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting