

## EUROLITE LED KLS-902 Next Compact Light Set

Bar with 4 powerful RGB/WW spots, QuickDMX support, IR remote control and carrying bag

Art. No.: 42109860

GTIN: 4026397673166



List price: 570.01 €

incl. 19% VAT.

### Features:

- 5 powerful LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix) spots controlled separately
- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- With a beam angle of 16°
- 20 integrated show programs
- Color blend stepless; Dimmer electronic; program selection
- Mounting points and power outlets for additional fixtures
- Control via DMX; stand-alone; Sound to light via Microphone; IR remote control; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- For application areas such as: Mobile use; Stage; mobile djs / entertainer; small rental; Rental
- Preprogrammed in EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light J; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- Very quiet working noise
- Application possibility: Suspended; on stand

#### Package contents

- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x omega bracket, 1 x declaration of conformity, 4 x knurled screw, 1 x bag

### Logistic

EAN / GTIN: 4026397673166

Weight: 10,80 kg

Length: 1.13 m

Width: 0.38 m

Height: 0.18 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 125 W

|                                |   |
|--------------------------------|---|
| IP classification:             | IP20  |
| Power connection:              | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)   |
| Cable length:                  | 3 m   |
| Power output:                  | 2 x IEC connector (F) mounting version<br>1 x P-Con (gray), mounting version  |
| Device fuse:                   | 5 x 20 mm, T 2 A Fuse replaceable   |
| Power output fuse per channel: | 5 x 20 mm, T 5 A Fuse replaceable   |
| Battery:                       | 1 x Button cell 3.0 V CR2025 lithium manganese<br>built-in  |
| Lamp type:                     | LED lamp  |
| LED:                           | 5 x 7 W high-power 4in1 QCL RGB/WW<br>(homogenous color mix)  |
| DMX channels:                  | 3; 4; 6; 8; 16; 20; 18  |
| DMX input:                     | 3-pin XLR (M) mounting version  |
| DMX output:                    | 3-pin XLR (F) mounting version  |
| Cooling:                       | Passive convection cooling  |
| Control:                       | DMX; stand-alone; Sound to light via Microphone;<br>IR remote control; Wireless footswitch (optional);<br>QuickDMX via USB (optional); W-DMX by<br>wireless solution via USB (optional); CRMX by<br>LumenRadio via USB (optional) |
| Preprogrammed in:              | EASY SHOW 1; LED EASY OPERATOR<br>DELUXE; Light Captain; EASY SHOW 2; Light J;<br>EASY SHOW 3   |
| Beam angle:                    | 16°   |
| Beam angle (1/2 peak):         | 16°   |
| Beam angle (1/10 peak):        | 32°   |
| Housing color:                 | Black   |
| Attachment system:             | TV spigot Ø 28mm<br>Omega bracket   |
| Dimensions:                    | Width: 1,08 m<br>Depth: 6 cm<br>Height: 28 cm   |
| Weight:                        | 9,80 kg   |
| Noise classification:          | Class 1 (very slight noise, suitable for noise-<br>sensitive environments)  |
| Legal specifications           |   |
| Special product:               | Not designed for household room illumination  |
| Intended use:                  | Show effect lighting  |