

## EUROLITE LED KLS Scan Next FX Compact Light Set

Compact bar with derby, spots, scanners, UV effect, QuickDMX port and bag

Art. No.: 42109897

GTIN: 4026397690064



**List price: 950.81 €**

incl. 19% VAT.

### Features:

- DMX light effect bar with 1 rotating LED derby, 4 LED spots, 2 scanners and UV LEDs
- Ultra-light, ideally suited for mobile use
- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- Comes pre-assembled with practical transport bag
- Several diverse DMX modes for various consoles and requirements
- LED derby and LED spots individually tiltable and controllable
- Mirror movement can be inverted separately for both scanners (e.g. for common, counter-rotating control)
- Brand-new software design with smart programs
- When fog is used, this effect becomes especially attractive
- Mains input and output for power linking up to 8 units
- 20 integrated Showprograms
- Can be operated in 3; 7; 13; 14; 15; 18; 19; 30; 32; 39 CH mode
- The device is cooled by cooling fan
- Controlling by DMX; IR remote control (provided); Sound to light via Microphone; stand-alone; Master/slave function; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control; Sound to light
- Preprogrammed in Light Captain
- With a beam angle of 15°
- With Mounting bracket
- OLED display for easy controlling
- For application areas such as: Wedding/gala; Lender; Small lender

### Logistic

EAN / GTIN: 4026397690064

Weight: 13,80 kg

Length: 1.15 m

Width: 0.17 m

Height: 0.52 m

#### spotlight

- 3 powerful LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)

#### light effect

- 1 powerful LED 3 W R/G/B  
**moving light**
- 1 powerful LED 15 W cold white (CW)  
**bar**
- 4 powerful LEDs 1 W high-power ultra violet (UV)

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	115 W
IP classification:	IP20
Protection class:	Class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A Fuse replaceable
Lamp type:	LED lamp
Equipment:	Color wheel; gobo wheel with static gobos
DMX channels:	3; 7; 13; 14; 15; 18; 19; 30; 32; 39
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; IR remote control (provided); Sound to light via Microphone; stand-alone; Master/slave function; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Light Captain; IR remote control; Sound to light
Beam angle:	15°
Beam angle (1/2 peak):	Spot 15°
Beam angle (1/10 peak):	Spot 28°
Illuminance in Lux (lx):	Red (R) 1m: 1022 lx, 3m: 125 lx, 6m: 33 lx Green (G) 1m: 2448 lx, 3m: 285 lx, 6m: 75 lx Blue (B) 1m: 395 lx, 3m: 47 lx, 6m: 13 lx Warm white (WW) 1m: 1892 lx, 3m: 219 lx, 6m: 58 lx All 1m: 4853 lx, 3m: 676 lx, 6m: 175 lx
Housing color:	Black
Attachment system:	TV spigot Ø 28mm 2x Mounting bracket
Display type:	OLED display
Dimensions:	Width: 1,1 m Depth: 15,5 cm Height: 43 cm
Weight:	12,80 kg
Spotlight	
LED:	Spot each 3 x 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
Light effect	

LED:	Multi beam effect each 1 x 3 W R/G/B
Moving light	
LED:	Scanner each 1 x 15 W cold white (CW)
Bar	
LED:	4 x 1 W high-power ultra violet (UV)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting