# eurolite®

## EUROLITE LED KLS PARty Compact Light Set

Compact LED spotlight set including transport bag

Art. No.: 42110197 GTIN: 4026397647266





6666

# The article is no longer in our assortment.

#### Features:

- Complete LED light set with four compact LED spots
- Crossbar with integrated DMX control unit and stand sleeve
- Suited for installation on a speaker stand (not included) or truss
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 12 bright 1 W LEDs (3 x R, 3 x G, 3 x B, 3 x W) per spot
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Via DMX, each spot can be controlled individually
- Additional controlling possibility via the EUROLITE IR-30 remote control, included in delivery
- Addressing and setting via control panel with 4-digit LED display
- Functions: RGBW color mixture, color presets, built-in programs, strobe effect with variable speed, dimmer, Master/Slave operation
- Black lacquered metal version
- IEC terminals for power linking up to 8 units
- 12 powerful LEDs 1 W high-power R/G/B/W<BR> spots controlled separately
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in EASY SHOW 1; Light J; LED PC-Control 512; Light Captain
- Flicker-free

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x bag

#### Logistic

EAN / GTIN: 4026397647266 Weight: 5,00 kg Length: 0.75 m Width: 0.23 m Heigth: 0.14 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	48 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 1 W high-power R/G/B/W
DMX channels:	5; 8; 20
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	EASY SHOW 1; Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Housing color:	Black
Attachment system:	Ø 35mm
Dimensions:	Length: 74 cm
	Depth: 12 cm
	Height: 22 cm
Weight:	3,60 kg
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting