

EUROLITE LED KLS PARTY Compact Light Set

Compact LED spotlight set including transport bag

Art. No.: 42110197

GTIN: 4026397647266



The article is no longer in our assortment.

Features:

- Complete LED light set with four compact LED spots
- Crossbar with integrated DMX control unit and stand sleeve
- Suited for installation on a speaker stand (not included) or truss
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 12 bright 1 W LEDs (3 x R, 3 x G, 3 x B, 3 x W) per spot
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Via DMX, each spot can be controlled individually
- Additional controlling possibility via the EUROLITE IR-30 remote control, included in delivery
- Addressing and setting via control panel with 4-digit LED display
- Functions: RGBW color mixture, color presets, built-in programs, strobe effect with variable speed, dimmer, Master/Slave operation
- Black lacquered metal version
- IEC terminals for power linking up to 8 units
- 12 powerful LEDs 1 W high-power R/G/B/W
 spots controlled separately
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in EASY SHOW 1; Light´J; LED PC-Control 512; Light Captain
- Flicker-free

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x bag

Logistic

EAN / GTIN: 4026397647266

Weight: 5,00 kg

Length: 0.75 m

Width: 0.23 m

Height: 0.14 m

Technical specifications:

| | |
|----------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 48 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 12 x 1 W high-power R/G/B/W |
| DMX channels: | 5; 8; 20 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; sound to light via microphone |
| Preprogrammed in: | EASY SHOW 1; Light`J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Housing color: | Black |
| Attachment system: | Ø 35mm |
| Dimensions: | Length: 74 cm Depth: 12 cm Height: 22 cm |
| Weight: | 3,60 kg |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |