

EUROLITE LED PARty Hybrid Spot

LED effect spotlight with RGB LEDs and stroboscope

Art. No.: 42110198

GTIN: 4026397651911



Features:

- 3 LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
- 18 LEDs 0.5 W SMD 5730 cold white (CW)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 3 integrated show programs
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; stand-alone
- Fixtures available for Light J; LED PC-Control 512; Light Captain; Colorchief
- With a beam angle of 22°
- With double bracket
- 4 digit 7-segment LED display
- For application areas such as: Decoration; mobile djs / entertainer; party room
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397651911

Weight: 0,61 kg

Length: 0.17 m

Width: 0.16 m

Height: 0.13 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	16 W
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug

Lamp type:	LED lamp
LED type:	3 x 3 W high-power 3in1 TCL RGB (homogenous color mix) 18 x 0.5 W SMD 5730 cold white (CW)
DMX channels:	7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; sound to light via microphone; stand-alone
Fixtures available for:	Light J; LED PC-Control 512; Light Captain; Colorchief
Beam angle:	22°
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	37°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic
Dimensions:	Width: 15.2 cm Depth: 12 cm Height: 17 cm
Weight:	0.52 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø10mm
Material:	Metal, 1 mm
Cable construction:	2 x 0.75 mm ² H03VVH2-F
Cable length:	Approx. 0.9 m
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x user manual