

EUROLITE Set 4x LED PARty Spot Silent RGB/WW with Soft Bag

Compact spotlight with 12 x 5 W 4in1 QCL RGB/WW LED and DMX control

Art. No.: 42110204 GTIN: 4026397724882









List price: 284.41 €

incl. 19% VAT.

Features:

- 12 powerful LEDs 5 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change programs; Dimmer electronic
- Strobe effect
- 10 integrated show programs
- Direct color selection for 20 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light'J; Light Captain; LED PC-Control 512
- Flicker-free
- The article is delivered with practical transport bag
- With a beam angle of 12°
- With double bracket
- 4 digit 7-segment LED display
- 4 pieces per set
- For application areas such as: Wedding/gala/events; party room; mobile djs / entertainer
- Silent operation

Package contents

- 4 x device, 1 x user manual, 1 x remote control, 1 x battery, 1 x bag

Technical specifications:

Power supply:

100-240 V AC, 50/60 Hz

Logistic

EAN / GTIN: 4026397724882

Weight: 2,90 kg Length: 0.41 m Width: 0.17 m Heigth: 0.21 m

| Protection class: Protection class | Power consumption: | 17 W |
|--|--------------------------|--|
| Power connection: Fixed power supply cord with Euro plug Device fuse: T 1 A fuse fix in power supply LED lamp LED type: LED lamp LED type: 12 x 5 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix) Flash rate: 0,5 - 16 Hz DMX channels: 4; 6; 8 DMX input: 3-pin XLR (M) mounting version DMX output: Cooling: Passive convection cooling Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); V-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by Wideley LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by Wideley LumenRadio via USB (optional); Via | IP classification: | IP20 |
| Device fuse: T 1 A fuse fix in power supply LED type: LED type: 12 x 5 W COB (chip-on-board) 4in1 QCL RGB/WW (hornogenous color mix) Flash rate: 0,5 - 16 Hz DMX channels: 4; 6; 8 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); CRMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by Widels USB (optional); Wid | Protection class: | Protection class II |
| LED lamp LED type: | Power connection: | Fixed power supply cord with Euro plug |
| LED type: 12 x 5 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix) Flash rate: 0,5 - 16 Hz DMX channels: 4; 6; 8 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); LeD PC-Control 512 Projection: Beam angle: 12° Beam angle: | Device fuse: | T 1 A fuse fix in power supply |
| RGB/WW (homogenous color mix) Flash rate: 0,5 - 16 Hz DMX channels: 4; 6; 8 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); VI-DMX by Wireless Solution via USB (optional); VI-DMX by Wireles | Lamp type: | LED lamp |
| DMX channels: DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); W-DMX by LumenRadio via USB (optional); CRMX by Lumenter Solution; CRMX by LumenRadio via USB (optional); CRMX by Lumenter Solution; CRMX by LumenRadio via USB (optional); CRMX by Lumenter Solution; CRMX by Lumenter Solution; CRMX by LumenRadio via USB (optional); CRMX by Lumenter Solution; CRMX by Lumenter Solution; CRMX by LumenRadio via USB (optional); CRMX by Lumenter Solution; CRMX by Lumenter Solution; CRMX by Lumenter Solution; CRMX by Lumenter Solution, CRMX by Lumenter Solution; CRMX by Lumenter Solution | LED type: | |
| DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional) Preprogrammed in: Light' J; Light Captain; LED PC-Control 512 Projection: Flicker-free PWM frequency: 2000 Hz Beam angle: 12° Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Flash rate: | 0,5 - 16 Hz |
| DMX output: 3-pin XLR (F) mounting version Passive convection cooling Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional) Preprogrammed in: Light'J; Light Captain; LED PC-Control 512 Projection: Flicker-free PWM frequency: 2000 Hz Beam angle: 12° Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 40° Beam angle (1/10 peak): Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Legal specifications Special product: Not designed for household room illumination | DMX channels: | 4; 6; 8 |
| Cooling: Passive convection cooling Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional) Preprogrammed in: Light'J; Light Captain; LED PC-Control 512 Projection: Flicker-free PWM frequency: 2000 Hz Beam angle: 12° Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 40° Beam angle (1/10 peak): Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Legal specifications Special product: Not designed for household room illumination | DMX input: | 3-pin XLR (M) mounting version |
| Control: Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional | DMX output: | 3-pin XLR (F) mounting version |
| master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio via USB (optional) Preprogrammed in: Light'J; Light Captain; LED PC-Control 512 Projection: Flicker-free PWM frequency: 2000 Hz Beam angle: 12° Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Metail: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Cooling: | Passive convection cooling |
| Projection: Flicker-free PWM frequency: 2000 Hz Beam angle: 12° Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Control: | master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by |
| PWM frequency: Beam angle: 12° Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 30° Housing color: Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Preprogrammed in: | Light´J; Light Captain; LED PC-Control 512 |
| Beam angle: 12° Beam angle (1/2 peak): 12° Beam angle (1/10 peak): 30° Housing color: Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Projection: | Flicker-free |
| Beam angle (1/2 peak): Beam angle (1/10 peak): Beam angle (1/10 peak): Beam angle (1/10 peak): Black matte Attachment system: Double bracket Display type: 4 digit 7-segment LED display Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | PWM frequency: | 2000 Hz |
| Beam angle (1/10 peak): Housing color: Attachment system: Double bracket Display type: 4 digit 7-segment LED display Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Beam angle: | 12° |
| Housing color: Attachment system: Double bracket 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Beam angle (1/2 peak): | 12° |
| Attachment system: Double bracket Display type: 4 digit 7-segment LED display Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Beam angle (1/10 peak): | 30° |
| Display type: 4 digit 7-segment LED display Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Housing color: | Black matte |
| Dimensions: Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Attachment system: | Double bracket |
| Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm Weight: 2,60 kg Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Display type: | 4 digit 7-segment LED display |
| Noise classification: Class 0 (no noise at all) Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Dimensions: | Width: 15,5 cm Height: 19 cm |
| Mounting bracket Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Weight: | 2,60 kg |
| Diameter mounting holes: 2 x Ø6mm; 1 x Ø13mm Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Noise classification: | Class 0 (no noise at all) |
| Material: Metal, 1,5 mm Legal specifications Special product: Not designed for household room illumination | Mounting bracket | |
| Legal specifications Special product: Not designed for household room illumination | Diameter mounting holes: | 2 x Ø6mm; 1 x Ø13mm |
| Special product: Not designed for household room illumination | Material: | Metal, 1,5 mm |
| | Legal specifications | |
| Intended use: Show effect lighting | Special product: | Not designed for household room illumination |
| | Intended use: | Show effect lighting |