eurolite®

EUROLITE LED Color Curtain

White LED curtain with 4 high-power RGBW LEDs and QuickDMX support











The article is no longer in our assortment.

Features:

- Elegant white design
- Cutout for cable inlet
- 4 powerful LEDs 4in1 QCL RGB/WW
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 15 preset colors
- Control via DMX; sound to light via microphone; master/slave function; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light Captain; Light'J
- 3 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; installation; restaurants, bars and hotels
- Silent operation
- Application possibility: On stand; suspended
- Package contents
- 1 x device, 1 x user manual, 1 x power cord, 1 x textile cover

Technical specifications:

Power supply:

100-240 V AC, 50/60 Hz

Logistic

EAN / GTIN: 4026397671629 Weight: 5,60 kg Length: 0.46 m Width: 0.46 m Heigth: 0.22 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

25 W
IP20
Mains input via P-Con (blue), mounting version
1 x P-Con (gray), mounting version
LED lamp
4 x 4in1 QCL RGB/WW
0 - 20 Hz
4; 8
1 x 3-pin XLR (M) mounting version
1 x 3-pin XLR (F) mounting version
DMX; sound to light via microphone; master/slave function; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light Captain; Light J
White
3 digit 7-segment LED display
Height: 130 cm
Diameter: Ø 40 cm
•
Diameter: Ø 40 cm
Diameter: Ø 40 cm 4,60 kg
Diameter: Ø 40 cm 4,60 kg