

EUROLITE LED Outdoor Spot 15W RGBW QuickDMX with stake

Weather-proof LED spotlight (IP65) with 15 W LED, incl. IR remote control, frost filter & ground stake

Art. No.: 50498638

GTIN: 4026397696301



List price: 224.91 €

incl. 19% VAT.

Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Additional frost filter provides a wide, soft and homogeneous light
- 1 powerful LED 15 W 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; QuickDMX; master/slave function; stand-alone; sound to light via microphone; DMX
- 3 buttons on the remote control for saving your own settings
- Flicker-free
- Easy installation
- With a beam angle of 9°
- With mounting bracket
- LCD display
- Suitable for outdoor use IP65
- Preprogrammed in Light Captain; Light´J
- With pressure compensation membrane
- Silent operation
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Suspended; standing; on stand

Package contents

Logistic

EAN / GTIN: 4026397696301

Weight: 1,80 kg

Length: 0.26 m

Width: 0.23 m

Height: 0.15 m

- 1 x light effect, 1 x stake, 1 x remote control, 1 x frost filter, 1 x screw, 2 x washer, 1 x declaration of conformity, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	16 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 1 m
Lamp type:	LED lamp
LED type:	1 x 15 W 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
Cooling:	Passive convection cooling
Control:	IR remote control; QuickDMX; master/slave function; stand-alone; sound to light via microphone; DMX
Preprogrammed in:	Light Captain; Light´J
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Setup:	Easy installation
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	22°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Length: 14,3 cm Width: 11,0 cm Depth: 18,4 cm
Weight:	1,52 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm; 2 x Ø6,5mm
Material:	Aluminum, 2 mm
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting