# eurolite®

### EUROLITE LED Neon Flex 24V 5m red Set

Flexible light tube with 600 LEDs, power supply unit, IP44

Art. No.: 50499903 GTIN: 4026397705171





## List price: 53.43 €

incl. 19% VAT.

#### Features:

- Extremely flexible light tube with silicone coating
- LED Neon Flex creates the effect of conventional neon light
- Continuously bright, uniform light without visible dots
- Ready-to-use set including power adapter, supply cable and mounting clips
- Easy plug-type system requires no complex installation
- Not shortenable or extendable
- 600 powerful LEDs red (R)
- Control via plug and play
- Suitable for outdoor use IP44
- Dimmable with certain dimmers (accessory)
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; installation; restaurants, bars and hotels
- Silent operation
- Application possibility: Wall mounting Package contents
- 1 x illuminant, 1 x external mains adapter, 10 x fixation clip, 10 x screw, 1 x user manual

#### **Technical specifications:**

Power supply:	24V DC
Power consumption:	20 W
IP classification:	IP44
Protection class:	Protection class III

#### Logistic

EAN / GTIN: 4026397705171 Weight: 0,93 kg Length: 0.18 m Width: 0.18 m Heigth: 0.07 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

ower connection:	Mains input via 2-pin screw plug connector (M) IP
able length:	Approx. 1,6 m
mp specification:	Dimmable with certain dimmers (accessory)
D type:	600 x red (R)
ght emission:	Top 9 mm
	Bottom 1,5 mm
ontrol:	Plug and play
blor of light:	Red
mps/meter:	120 pc/pcs
ower/meter:	4 W
mps/tube:	600 pc/pcs
mp life:	30000 h
busing color:	Semi-transparent
mensions:	Length: 500 cm
	Width: 1 cm
	Height: 1,6 cm
eight:	0,85 kg
bise classification:	Class 0 (no noise at all)
ternal mains adapter	
ower supply:	230 V AC, 50 Hz
classification:	IP44
otection class:	Protection class II
onnections:	Output: screw plug-in terminal
utput:	24 V DC; 1 A; 24 W
blor:	Black
eight:	0,1 kg
kation clip	
ameter mounting holes:	1 x Ø3mm
aterial:	Plastic
blor:	Semi-transparent