eurolite®

EUROLITE LED IP Strip 150 5m 6500K 12V

Flexible LED strip for indoor and outdoor use

Art. No.: 50530170 GTIN: 4026397426748





The article is no longer in our assortment.

Description:

With its numerous IP LED strips, Eurolite offers light on tape for outdoor use. Eurolite presents different stripes fulfilling the IP68 standard.

The flexible LED strips have a length of 5 meters. Unichrome versions - red, blue, green, yellow, cool white, warm white - are complimented by two RGB versions. The single colors can be ordered either with a wide span (150 LEDs) or with a short span (300 LEDs) between the LEDs. The RGB versions are available in 12 V or 24 operation - LED quantities are always 150. An optional LED controller controls the brightness and the speed of the RGB LEDs or provides automatic run of the built-in color programs.

Supplied on a plastic reel, the LED stripes feature a self adhesive rear side for simple installation. Color and form can be used as desired as the strips are very flexible and adaptable to really every venue.

Features:

- Flexible LED strip for decorative lighting
- Perfect for indirect lighting, custom-made versions for fair or shop applications as well as all kinds of background lighting
- For indoor and outdoor use (IP44)
- Can be cut into segments of variable size (groups of 3 LEDs)
- Self-adhesive rear side
- Supplied on a plastic reel
- Matching control units and power units optionally available
- Different versions available
- Suitable for outdoor use IP44

Logistic

EAN / GTIN: 4026397426748 Weight: 0,19 kg Length: 0.20 m Width: 0.20 m Heigth: 0.01 m

Technical specifications:

Power consumption:	10 W
IP classification:	IP44
Standing/fixation:	Self adhesive
Lamps/meter:	30 pc/pcs
Power/meter:	2,4 W
Lamps/tube:	150 pc/pcs
Lamp distance:	33 mm
Cutting mark:	10 cm
Housing color:	White
Dimensions:	Length: 5 m
	Width: 1 cm
Weight:	180 g
Watts per meter/total:	2.4 W/max. 10 W
Protection grade:	IP44
LED type:	SMD 3528
LED number:	150
Color temperature:	6400 K
Cutting mark:	every 100 mm
Dimensions:	Ø 10 mm x 5000 mm