eurolite®

EUROLITE LED Strip RGB DMX512 Controller

3-channel LED controller with DMX interface for RGB LEDs 12-24 V

Art. No.: 50530554 GTIN: 4026397518818



The article is no longer in our assortment.

Features:

- Compact 3-channel LED controller for controlling RGB LEDs (12-24 V) via DMX
- Converts standard DMX512 signals to PWM signals for driving LEDs
- DMX input and parallel DMX output for serial connection via XLR and RJ45 connectors
- Stand-alone operation possible with 9 built-in programs (7 individual colors and 2 color changing programs with adjustable speed)
- DMX addressing and settings via DIP switches
- Plug-in screw terminals for connecting the LEDs and the power supply (accessory)
- Rugged black metal housing
- Control via DMX
- Interface

Technical specifications:

Power supply:	12V AC
	Or
	24V DC
IP classification:	IP20
Power connection:	Mains input via screw terminal
Power output:	1 x screw terminal
DMX channels:	3
DMX input:	1 x RJ14 (F) mounting version
	1 x 3-pin XLR (M) mounting version

Logistic

EAN / GTIN: 4026397518818 Weight: 0,35 kg Length: 0.17 m Width: 0.09 m Heigth: 0.05 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

DMX output:	1 x 3-pin XLR (F) mounting version
	1 x RJ14 (F) mounting version
Control:	DMX
Color:	Black
Housing design:	Interface
Dimensions:	Width: 16,5 cm
	Depth: 4 cm
	Height: 7,5 cm
Weight:	0,31 kg
Standby current:	<1 W
Output power:	max. 144 W (12 V), 288 W (24 V)
Output current:	max. 4 A per channel (12 A total)