eurolite®

EUROLITE LED MSB-8i Bar

Moving Bar with narrow beams and 4 lenses on the front and backside

Art. No.: 50900751 GTIN: 4026397595178









The article is no longer in our assortment.

Features:

- Equipped with eight 8 W quadcolor LEDs with RGBW colors
- With Infinity function for unlimited TILT movement
- Positioning within 360° TILT
- Automatic position correction
- Exact positioning via 16-bit TILT movement resolution
- Individual control of each LED
- Narrow beam angle
- Stepless color blend, color change, preset colors for each LED, dimmer and strobe effect
- Stand-alone, master/slave and DMX mode
- Control panel with LC display for easy configuration
- Mains input and output for power linking up to 8 units
- 8 powerful LEDs 8 W high-power 4in1 QCL RGBW
- Multi beam effect
- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 1°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20

Logistic

EAN / GTIN: 4026397595178 Weight: 6,75 kg Length: 0.70 m Width: 0.18 m Heigth: 0.27 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	8 x 8 W high-power 4in1 QCL RGBW
Max. TILT movement:	360° exact positioning (16 bit resolution) plus infinity auto position correction (feedback)
Flash rate:	0 - 13 Hz
DMX channels:	45; 21; 12; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; stand-alone; sound to light via microphone
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	1°
Beam angle (1/2 peak):	1°
Housing color:	Black
Dimensions:	Length: 62,9 cm
	Depth: 10,6 cm
	Height: 18,1 cm
Weight:	6,10 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting