

EUROLITE LED MFX-1 Beam Effect

Small moving effect with 3 lenses in RGBW and unlimited TILT movement

Art. No.: 50944301

GTIN: 4026397571493



The article is no longer in our assortment.

Features:

- With Infinity function for unlimited TILT movement
- Equipped with three 10 W quadcolor LEDs with RGBW colors
- Narrow beam angle
- Compact lightweight
- Functions: Colored beams in R, G, B and W, auto mode, sound control, color presets, Master/Slave function, built-in programs
- Stepless RGBW color mixture
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Feed-through output allows to power up to 8 devices
- Ready for connection with power cord and safety plug
- LED: 3 x high-power 10 W 4in1 QCL RGBW
- Can be operated in 16 CH mode
- The device is cooled by cooling fan
- Controlling by stand-alone; DMX; Sound to light via Microphone
- Preprogrammed in Light 'J'; LED PC-Control 512
- Flicker-free projection
- Effect: Multi beam effect

Logistic

EAN / GTIN: 4026397571493

Weight: 2,80 kg

Length: 0.35 m

Width: 0.20 m

Height: 0.26 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	35 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	3 x high-power 10 W 4in1 QCL RGBW
Max. TILT movement:	Exact positioning (16 bit resolution) plus infinity
Max. PAN movement:	Exact positioning (16 bit resolution) 540°
Flash rate:	0 - 18 Hz
DMX channels:	16
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; Sound to light via Microphone; Light J; LED PC-Control 512
Beam angle:	2°
Beam angle (1/2 peak):	2°
Illuminance in Lux (lx):	Red (R) 3m: 913 lx, 6m: 182 lx Green (G) 3m: 915 lx, 6m: 228 lx Blue (B) 3m: 252 lx, 6m: 63 lx Cold white (CW) 3m: 936 lx, 6m: 232 lx
Housing color:	Black
Dimensions:	Width: 18,9 cm Depth: 14,9 cm Height: 29,3 cm
Weight:	2,28 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting