

### **EUROLITE LED MFX-1 Beam Effect**

Small moving effect with 3 lenses in RGBW and unlimited TILT movement

**Art. No.: 50944301** GTIN: 4026397571493











## The article is no longer in our assortment.

#### Features:

- With Infinity function for unlimited TILT movement
- Equipped with three 10 W quadcolor LEDs with RGBW colors
- Narrow beam angle
- Compact lightweight
- Functions: Colored beams in R, G, B and W, auto mode, sound control, color presets, Master/Slave function, built-in programs
- Stepless RGBW color mixture
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Feed-through output allows to power up to 8 devices
- Ready for connection with power cord and safety plug
- 3 powerful LEDs 10 W high-power 4in1 QCL RGBW
- Exact positioning (16 bit resolution)
- Multi beam effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 2°

## Logistic

EAN / GTIN: 4026397571493

Weight: 2,80 kg Length: 0.35 m Width: 0.20 m Heigth: 0.26 m

# **Technical specifications:**

| Power supply:            | 100-240 V AC, 50/60 Hz   |
|--------------------------|--|
| Power consumption:       | 35 W   |
| IP classification:       | IP20   |
| Power connection:        | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)   |
| Power output:            | 1 x IEC connector (F) mounting version   |
| Lamp type:               | LED lamp   |
| LED type:                | 3 x 10 W high-power 4in1 QCL RGBW  |
| Max. TILT movement:      | Exact positioning (16 bit resolution) plus infinity  |
| Max. PAN movement:       | 540° exact positioning (16 bit resolution)   |
| Flash rate:              | 0 - 18 Hz  |
| DMX channels:            | 16   |
| DMX input:               | 1 x 3-pin XLR (M) mounting version   |
| DMX output:              | 1 x 3-pin XLR (F) mounting version   |
| Cooling:                 | Cooling fan  |
| Control:                 | Stand-alone; DMX; sound to light via microphone  |
| Preprogrammed in:        | Light'J; LED PC-Control 512; Light Captain   |
| Projection:              | Flicker-free   |
| Beam angle:              | 2°   |
| Beam angle (1/2 peak):   | 2°   |
| Illuminance in Lux (lx): | Red (R) 3m: 913 lx, 6m: 182 lx<br>Green (G) 3m: 915 lx, 6m: 228 lx<br>Blue (B) 3m: 252 lx, 6m: 63 lx<br>Cold white (CW) 3m: 936 lx, 6m: 232 lx |
| Housing color:           | Black  |
| Dimensions:              | Width: 18,9 cm<br>Depth: 14,9 cm<br>Height: 29,3 cm  |
| Weight:                  | 2,28 kg  |
| Legal specifications     |  |
| Special product:         | Not designed for household room illumination   |
| Intended use:            | Show effect lighting   |