

## EUROLITE LED MFX-8 Action Barrel

LED barrel, unlimited PAN/TILT movement, 15 W 4in1 LEDs in RGBW

Art. No.: 50944323

GTIN: 4026397592733

**The article is no longer in our assortment.**

### Features:

- Beam effect with 9 lenses with 10 W quadcolor LEDs in RGBW colors arranged in 3 rows
- Compact lightweight
- With Infinity function for unlimited TILT movement
- Positioning within 630° PAN and 200° TILT
- PAN-angle switchable between 630° and 540°
- Functions: Colored beams, auto mode, color presets, color change, Master/Slave function, built-in programs, stepless RGBW color mixture - each LED row can be controlled individually
- Masterdimmer
- Strobe effect with 1-25 flashes per second and with adjustable speed
- Random strobe effect
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection with power cord and safety plug
- 9 powerful LEDs 10 W high-power 4in1 QCL RGBW
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Multi beam effect
- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in LED PC-Control 512; Light Captain; Light 'J
- Flicker-free
- With a beam angle of 9°

### Logistic

EAN / GTIN: 4026397592733

Weight: 6,65 kg

Length: 0.39 m

Width: 0.32 m

Height: 0.21 m

## Technical specifications:

|                        |  |
|------------------------|--|
| Power supply:          | 100-240 V AC, 50/60 Hz   |
| Power consumption:     | 130 W  |
| IP classification:     | IP20   |
| Power connection:      | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Lamp type:             | LED lamp   |
| LED type:              | 9 x 10 W high-power 4in1 QCL RGBW  |
| Max. TILT movement:    | 200° exact positioning (16 bit resolution) plus infinity auto position correction (feedback)     |
| Max. PAN movement:     | 540°, 630° exact positioning (16 bit resolution) auto position correction (feedback)             |
| Flash rate:            | 0 - 25 Hz  |
| DMX channels:          | 12; 22   |
| DMX input:             | 1 x 3-pin XLR (M) mounting version   |
| DMX output:            | 1 x 3-pin XLR (F) mounting version   |
| Control:               | DMX; stand-alone; sound to light via microphone  |
| Preprogrammed in:      | LED PC-Control 512; Light Captain; Light´J   |
| Projection:            | Flicker-free   |
| Beam angle:            | 9°   |
| Beam angle (1/2 peak): | 9°   |
| Housing color:         | Black  |
| Dimensions:            | Width: 25,5 cm<br>Depth: 13,5 cm<br>Height: 32,5 cm  |
| Weight:                | 5,95 kg  |
| Legal specifications   |  |
| Special product:       | Not designed for household room illumination   |
| Intended use:          | Show effect lighting   |