

ANTARI DarkFX Drive 4 MK2

DMX control unit for a total of 4 Antari DarkFX Strips or DarkFX Spots

Art. No.: 51100824 GTIN: 4719850658182





The article is no longer in our assortment.

Description:

The Antari DarkFX Drive 4 MKII is a compact driver exclusively designed for the Antari DarkFX high-power UV fixtures.

Equipped with 4 bare wire terminal blocks for up to 4 fixtures, it can be used to adjust dimmer brightness and strobe speed.

The DarkFX Drive 4 MKII is operated in one of two modes: Either in DMX mode with 2 channels via the 5-pin XLR connectors (with RDM support) or in stand-alone mode via the LCD display and the 4 operating buttons. Use the powerCON input to connect it to the mains.

Features:

- Terminal blocks support four fixtures
- The device is cooled by passive convection cooling
- Control via RDM; DMX; stand-alone
- Built with NEUTRIK connector
- Dimmer curves adjustable

Package contents

- 1 x device, 1 x user manual, 1 x power cord

Technical specifications:

| Power supply: | 100-240 V AC, 50/60 Hz |
|--------------------|------------------------|
| Power consumption: | 75 W |
| IP classification: | IP20 |

Logistic

EAN / GTIN: 4719850658182

Weight: 2,20 kg Length: 0.28 m Width: 0.23 m Heigth: 0.18 m

| DMX channels: | 2 |
|----------------|------------------------------------|
| DMX input: | 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 5-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | RDM; DMX; stand-alone |
| Housing color: | Black |
| Use of brands: | Built with NEUTRIK connector |
| Dimensions: | Width: 16,7 cm |
| | Depth: 21,1 cm |
| | Height: 7 cm |
| Weight: | 1,77 kg |