



The article is no longer in our assortment.

Features:

- Rugged housing and an appealing style in A1 quality
- Integrated starter
- Ready for connection with power cord, ON/OFF-switch on the housing, and Euro plug
- High illumination
- Easy installation
- Delivered with mounting materials and installed UV tube
- Perfect in public places or for home use
- UV effect
- Control via on/off switch on device
- With a beam angle of 270°

Package contents

- 1 x device, 1 x illuminant, 1 x power cord, 1 x adapter cable, 2 x fixation clip, 2 x screw, 1 x user manual, 1 x mounting material

Logistic

EAN / GTIN: 4026397512335
Weight: 0,67 kg
Length: 1.22 m
Width: 0.07 m
Height: 0.03 m
Bulky product

Technical specifications:

| | |
|--------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 25 W |
| IP classification: | IP20 |
| Protection class: | Protection class II |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with Euro plug (provided) |

| | |
|------------------------|---|
| Cable length: | 1 m |
| Lamp type: | Fluorescent tube |
| Color generation: | Ultra violet (UV) |
| Control: | On/off switch on device |
| Beam angle: | 270° |
| Beam angle (1/2 peak): | UV effect 270° |
| Housing color: | Black |
| Material: | Plastic |
| Dimensions: | Length: 120,5 cm Width: 2,5 cm Height: 4,3 cm |
| Weight: | 0,50 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |