

## EUROLITE Complete Fixture 60cm 18W slim UV and white

Set, ready for connection with UV tube and cold white fluorescent tube

Art. No.: 51101462

GTIN: 4026397170108



### Features:

- UV tube with casing, power cord and power plug
- Minimal housing
- High ultraviolet light
- Warm-up time approx. 3 min
- UV effect
- Control via plug and play
- With a beam angle of 270°
- For application areas such as: Decoration; party room; restaurants, bars and hotels

### Logistic

EAN / GTIN: 4026397170108

Weight: 0,57 kg

Length: 0.68 m

Width: 0.09 m

Heigh: 0.04 m

### Technical specifications:

|                     |  |
|---------------------|--|
| Power supply:       | 230 V AC, 50 Hz                        |
| Power consumption:  | 20 W                                   |
| IP classification:  | IP20                                   |
| Protection class:   | Protection class II                    |
| Power connection:   | Fixed power supply cord with Euro plug |
| Cable construction: | 2 x 0.75 mm <sup>2</sup> H03VVH2-F     |
| Cable length:       | Approx. 1.5 m                          |
| Lamp type:          | Fluorescent tube                       |
| Color generation:   | Cold white (CW); ultra violet (UV)     |

|                                  |  |
|----------------------------------|--|
| Control:                         | Plug and play                                    |
| Beam angle:                      | 270°   |
| Beam angle (1/2 peak):           | 270°   |
| Color temperature:               | 6000K  |
| Lead time:                       | 180 s  |
| Construction:                    | Tube T8  |
| Burning position:                | P30 (horizontal ±30°)                            |
| Wavelength:                      | Ultra violet (UV) 365 nm; cold white (CW) 545 nm |
| Housing color:                   | Black  |
| Diameter mounting holes:         | 2 x Ø4mm   |
| Material:                        | Aluminum   |
| Dimensions:                      | Length: 63.5 cm<br>Width: 3.5 cm<br>Height: 6 cm |
| Weight:                          | 0.47 kg  |
| Photobiological safety:          | Risk Group 0                                     |
| Energy efficiency class (A - G): | G  |

### **Scope of delivery:**

- 1 x device
- 2 x illuminant
- 2 x mounting material
- 2 x screw
- 1 x user manual