eurolite®

EUROLITE UV-active paint, green 100ml

UV active color with high brightness

Art. No.: 51107600

GTIN: 4026397015003



The article is no longer in our assortment.

Features:

- For highlighting individual object parts
- Easy processing
- Simple means - big effect
- Paintings and bar decoration
- Discotheque truss systems decoration
- Applicable on all surfaces, e.g. wood, metal, plastic
- Outstanding opacity and coverage
- Very high luminosity as soon as the uv light falls on the lacquered object
- The optional EUROLITE primer increases luminosity
- The optional EUROLITE protection varnish preserves the color
- Easy application by brush, roller or sprayer
- High yield

Logistic

EAN / GTIN: 4026397015003
Weight: 0,15 kg
Length: 0.05 m
Width: 0.05 m
Heigth: 0.09 m

Technical specifications:

Practical coverage:	approx. 90-100 ml per m²
Dry time to touch:	apprx. 4-5 hours
Dry time to recoat:	approx. 24 hours
Applicable thinner:	Universal thinner
Contents:	Xylol, toluol, ethylbenzol, oropylbenzol, 1.3,5 trimethylbenzol, inflammable crude oil distillates
Boiling point:	135-160° C

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Flash point:	26° C
Ignition temperature:	450° C
Denstiy:	1-1.3 g / cm^3 (dependent on color)
Solvent percentage:	23 + 3%

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.