

EUROLITE AKKU FL-1 LED Flamelight

Weather-proof LED flame light effect

Art. No.: 51114540 GTIN: 4026397640106











The article is no longer in our assortment.

Description:

Weatherproof LED flame light effect

The romantic mood light with moving flame is ideally suited for use in your garden, terrace or balcony. The 96 built-in LEDs provide a pleasant, warm white light.

The supplied ground stake makes installation even in your garden very easy. A button for switching on and off can be found directly on the device.

You can charge the battery of your Flamelight easily with the Micro-USB cable. The operating time is up to 20 hours.

The plastic casing of the Flamelight is splash-proof (IP44).

Features:

- Romantic mood light with flickering flame
- Micro USB charging port (USB cable included)
- Durable plastic cabinet
- Cordless, flexible and versatile
- Battery operation up to 20h depending on program used
- 96 powerful LEDs amber (A)
- Control via on/off switch on device
- Easy installation
- For application areas such as: Wedding/gala/events; party room; Trade fair and shop fitting; theater
- Silent operation
- Application possibility: Standing; wall mounting

Logistic

EAN / GTIN: 4026397640106

Weight: 0,50 kg Length: 0.11 m Width: 0.16 m Heigth: 0.27 m

Package contents

- 1 x device, 1 x stake

Technical specifications:

IP classification:	IP44
Power connection:	Battery/battery pack
	Mains input via micro USB (F) mounting version power supply cord for USB A mains connection (provided)
Battery pack type:	1 x lithium ion 3,7 V, 2000 mAh,
Battery pack:	Battery operation up to 20h depending on program used
	Recharging time 3h
Lamp type:	LED lamp
LED type:	96 x amber (A)
Control:	On/off switch on device
Setup:	Easy installation
Housing color:	Black
Dimensions:	Height: 16,6 cm
	Diameter: Ø 10 cm
Weight:	0,36 kg
Noise classification:	Class 0 (no noise at all)
Stake	
Dimensions:	Length: 50 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting