MEANWELL LED Power Supply 240W / 24V IP67 HLG-240H-24

LED switching power supply IP67, 240 W / 24 V DC / 10 A

Art. No.: 51405006

GTIN: 4026397704112

List price: 129.71 €

incl. 19% VAT.

Features:

- Constant voltage, constant current
- Especially for LED lighting installations with high power requirements
- Full-range AC input
- Low-noise according to EMC standard EN 61000-3-2 class C
- Built-in active PFC filter
- Overload protection by shutdown, auto recovery
- Rugged metal housing
- Suitable for outdoor use IP67
- For further information about this product, please refer to the Data Sheet under "Downloads"
  Package contents
- 1 x external mains adapter

Logistic

EAN / GTIN: 4026397704112
Weight: 1,25 kg
Length: 0.31 m
Width: 0.10 m
Heigth: 0.05 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP67
Protection class:	Protection class I
Power connection:	Fixed Supply cord with open wires
Cable length:	0,32 m
Power output:	No connector/cable only
Housing color:	Silver

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Controls:	Overheat; overload; Overvoltage; short-circuit
Output:	24 V DC; 10 A; 240 W
Dimensions:	Length: 24,42 cm Width: 6,8 cm Height: 3,88 cm
Weight:	1,20 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.