# eurolite®

## **EUROLITE NB-60 ICE Low Fog Machine**


Compact low fog machine with 600 W, timer, ice cube cooling

Art. No.: 51701984 GTIN: 4026397606270









incl. 19% VAT.

### Features:

- Compact low fog machine
- A tank full and 2 kg ice will last for approx. 1.5 hours of fogging
- Adjustable timer with interval, duration and output volume
- Continuous output
- Manual fog output
- Water drainage valve system allows for easy cleanup
- Rugged metal housing
- Short warm-up time
- Output distance: Approx. 3 m
- Control via wired remote control
- For application areas such as: Wedding/gala/events; stage; theater; video and photography
- With level indication
- Operates on water-based fluid
- Removable tank
- Application possibility: Standing
- Package contents
- 1 x device, 1 x user manual, 1 x remote control, 1 x container, 1 x filter

### Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	600 W
IP classification:	IP20

#### Logistic

EAN / GTIN: 4026397606270 Weight: 8,40 kg Length: 0.51 m Width: 0.35 m Heigth: 0.34 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Fixed power supply cord with safety plug
Device fuse:	5 x 20 mm, F 4 A fuse replaceable
Warm-up time:	Approx. 2 min
Output distance:	Approx. 3 m
Tank capacity:	1,2 I water-based fluid removable tank
Fluid consumption:	Approx. 12 ml/min
Ice chamber:	2 kg
Control:	Wired remote control
Housing color:	Black; silver
Controls:	Overheat
Dimensions:	Width: 32 cm
	Depth: 26 cm
	Height: 26 cm
Weight:	7,45 kg
Noise classification:	Class 2 (slight noise)