

ANTARI X-515 MK2 Fogger & controller X-10 MK2

High performance fog machine X-515II

Art. No.: 51702635 GTIN: 4026397051506



The article is no longer in our assortment.

Features:

- Heavy-duty fog machine with exceptional components for long service life ideal for rental applications
- Creates pure, dry fog with high density
- Aluminum cast heater
- Silent heavy-duty pump
- Removable tank
- Electronic fluid level sensor
- Control via integrated DMX interface or supplied cable control module X-10II with LCD screen
- X-10II functions: timer with interval, duration and output volume; continuous output; manual activation; DMX starting address, heater and fan
- DMX interface with 3- and 5-pin connectors
- Metal housing with carrying handles
- Optional mounting bracket and drip tray
- Optional flightcase for touring applications
- Output distance: Approx. 15 m
- Big tank capacity

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	1500 W
Warm-up time:	Approx. 8,5 min
Output distance:	Approx. 15 m

Logistic

EAN / GTIN: 4026397051506 Weight: 16,30 kg Length: 0.75 m Width: 0.34 m Heigth: 0.33 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Tank capacity:	6
Fluid consumption:	Approx. 118 ml/min
Dimensions:	Width: 19 cm
	Depth: 65 cm
	Height: 24 cm
Weight:	14,80 kg
Smoke-output:	15 m
Fluid consumption:	8.5 min./liter (100 % output)
Output volume:	20000 cft/min. (approx. 570 m ³ /min.)
Warm-up time:	8.5 min.
Tank capacity:	6 liters
DMX connection:	5-pin and 3-pin XLR
Dimensions (L x W x H):	650 x 240 x 190 mm