

ANTARI DNG-50 Low Fog Machine

High performance low fog machine

Art. No.: 51702667

GTIN: 4710586557169



List price: 2378.81 €

incl. 19% VAT.

Description:

The DNG-50 delivers smooth, dry, ground-hugging fog using advanced ultrasonic technology-no dry ice or CO2 required. This dry-fog output minimizes moisture and residue, making it ideal for venues that demand clean, safe, and consistent atmospherics.

Designed for small to medium-sized spaces, the DNG-50 produces dense, stable low fog perfect for weddings, theaters, studios, themed attractions, and special events. Compact, quiet, and energy-efficient, it maintains an optimal mix ratio to keep fog low to the floor, creating immersive environments with ease.

Reliable for both permanent installations and mobile productions, the DNG-50 delivers professional-grade low-lying fog effects with exceptional consistency, cleanliness, and visual impact-bringing premium performance to any event.

Features:

- Creates large amounts of long-lasting low fog to fill up the venue in minutes
- No CO2 or dry ice is necessary due to ultrasonic technology, therefore inexpensive to operate
- The water is atomized by ultrasound and mixed with the fog particles
- User friendly - can be operated like any other fog machine
- Adjustable timer with interval, duration and output volume, continuous output, manual activation
- Short warm-up time
- Output distance: Approx. 3 m
- Big tank capacity
- Removable tank
- Operates on water-based fluid
- Can be operated in 1 CH mode

Logistic

EAN / GTIN: 4710586557169

Weight: 30,30 kg

Length: 0.93 m

Width: 0.47 m

Height: 0.63 m

Bulky product

- Control via stand-alone; timer; DMX; RDM; wireless remote control (optional); W-DMX by wireless solution (optional)
- Monochrome LCD display
- Rugged metal housing
- With accessory compartment
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: Standing

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	1200 W
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Warm-up time:	Approx. 2 min
Output volume:	Approx. 50 m ³ /min
Output distance:	Approx. 3 m
Tank capacity:	2.5 l water-based fluid removable tank 5 l water removable tank
Fluid consumption:	Approx. 16 ml/min
Fluid consumption:	Approx. 50 ml/min
DMX channels:	1
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Control:	Stand-alone; timer; DMX; RDM; wireless remote control (optional); W-DMX by wireless solution (optional)
Housing color:	Black
Operating principle:	Vaporizing fog machine mit ultrasonic vaporizer
Heater:	800 W
Display type:	Monochrome LCD display
Color:	Black
Dimensions:	Length: 86.5 cm Width: 35.5 cm Height: 51.7 cm
Weight:	25.40 kg
Noise classification:	Class 2 (slight noise)

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 2 x container
- 2 x tube