

EUROLITE Confetti Double Shot DMX

Electric firing unit with 2 channels and DMX control for confetti and streamers

Art. No.: 51707831

GTIN: 4026397738155



Description:

Confetti Double Shot DMX is a compact firing unit for confetti or streamer cannons of various brands. Two confetti and streamer cannons can be fired simultaneously or individually at the push of a button or via DMX signal. An additional safety channel prevents misfires in DMX mode. The projection angles of both cannons can be independently adjusted by 180° and rotated by 90°. The base plate provides a secure footing and M10 flying points for flexible mounting options.

Logistic

EAN / GTIN: 4026397738155

Weight: 8,90 kg

Length: 0.38 m

Width: 0.34 m

Height: 0.22 m

Features:

- The electric shooter can be used for confetti or streamer cannons
- Fires 2 cannons simultaneously or individually
- Suitable for electric cannons with 50 and 80 cm length
- The shooting angle can be adjusted steplessly
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Monochrome LCD display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: Standing; suspended

Technical specifications:

| | |
|--------------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | Max. 110 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x P-Con (gray), mounting version Bypass |
| Device fuse: | 5 x 20 mm, F 3 A fuse replaceable |
| DMX channels: | 3 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Housing color: | Black matte |
| Display type: | Monochrome LCD display |
| USB port: | 1 x type A |
| Diameter mounting holes: | 4 x Ø10mm |
| Use of brands: | Built with SEETRONIC connector |
| Material: | Metal, painted |
| Dimensions: | Length: 32.5 cm Width: 26.5 cm Height: 20 cm |
| Weight: | 8.30 kg |

Scope of delivery:

1 x device
1 x user manual
1 x power cord