

## EUROLITE LED FE-1750 Hybrid Laserflower

4in1 LED effect spotlight with derby, washlight, laser (2M) and strobe

Art. No.: 51741083

GTIN: 4026397642773



**List price: 272.51 €**

incl. 19% VAT.

### Features:

- Rotating derby for mirror ball effects with 6 high-power 3 W RGBAW+UV LEDs (6in1)
- 8 high-power 4 W RGB+UV LEDs (4in1) for washlight and blacklight effects
- 2 laser diodes for of red and green star laser effects
- Laser class 2M: does not require additional protective measures or appointment of a laser safety officer
- Strobe ring with 12 cold white 0.5 W SMD LEDs for fast, dynamic strobe effects
- All effects can be controlled individually
- 7 built-in auto and music show programs
- Stepless color blend, dimmer and strobe effect
- Control panel with LED display for easy configuration
- Convenient wireless control via included IR remote control
- Supports QuickDMX - the wireless DMX system from Eurolite
- Built-in phantom-powered USB port for QuickDMX, CRMX and WDMX receivers (optional)
- Swivel mounting bracket
- Mains input and output for power linking up to 8 units
- LED: Strobe effect 12 x SMD 0,5 W cold white (CW)
- LED: Multi beam effect 6 x high-power 3 W 6in1 HCL RGBWA/UV
- LED: UV effect 8 x high-power 4 W 4in1 QCL RGB/UV (homogenous color mix)
- Can be operated in 4; 13 CH mode
- The device is cooled by cooling fan
- Controlling by stand-alone; DMX; IR remote control; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in LED PC-Control 512; EASY SHOW; Light Captain
- Effect: Multi beam effect; flower effect; Strobe effect; UV effect; laser

### Logistic

EAN / GTIN: 4026397642773

Weight: 5,30 kg

Length: 0.35 m

Width: 0.34 m

Height: 0.28 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 0,5 A Fuse replaceable
Lamp type:	LED lamp
LED:	Strobe effect 12 x SMD 0,5 W cold white (CW) Multi beam effect 6 x high-power 3 W 6in1 HCL RGBWA/UV UV effect 8 x high-power 4 W 4in1 QCL RGB/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
Laser class:	Class 2M
Laser color:	R/G
Laser module:	Green (G) 50 mW 532nm Red (R) 100 mW 650nm
DMX channels:	4; 13
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; LED PC-Control 512; EASY SHOW; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Light Captain
Beam angle:	25°
Beam angle (1/2 peak):	25°
Housing color:	Black
Display type:	Monochrome 4 digits 7-segment LED display
Dimensions:	Width: 31,5 cm Depth: 19 cm Height: 33 cm
Weight:	4,75 kg
Noise classification:	Class 2 (slight noise)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in