

EUROLITE LED B-40 Laser Beam Effect wh

LED beam effect with RGBW color mixing and RG laser

Art. No.: 51741088 GTIN: 4026397666458









List price: 403.41 €

incl. 19% VAT.

Features:

- 2 laser diodes project hundreds of red and green laser beams
- 5 powerful LEDs 8 W high-power 4in1 QCL RGBW
3 segments controlled separately
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; rental
- Laser; multi beam effect; strobe effect
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- Rotation speed stepless; color blend stepless; Dimmer electronic
- 7 integrated show programs
- The device is cooled by cooling fan at the Head; cooling fan at the base
- Control via IR remote control; stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With mounting bracket
- Mains input and output for power linking up to 8 units
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light'J; Colorchief
- Application possibility: Standing; suspended; on stand

Package contents

 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x mounting bracket, 4 x screw, 4 x washer

Logistic

EAN / GTIN: 4026397666458

Weight: 6,35 kg Length: 0.39 m Width: 0.39 m Heigth: 0.49 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	65 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	5 x 8 W high-power 4in1 QCL RGBW
Flash rate:	0 - 20 Hz
Laser class:	2M
Laser color:	R/G
Laser module:	Green (G) 40 mW 532nm Red (R) 100 mW 650nm
DMX channels:	3; 10; 22
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan at the Head Cooling fan at the base
Control:	IR remote control; stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light'J; Colorchief
Housing color:	White
Attachment system:	Mounting bracket
Dimensions:	Width: 31 cm Depth: 31 cm
	Height: 39 cm
Weight:	4,30 kg
Noise classification:	Class 2 (slight noise)