

EUROLITE LED KLS Laser Bar FX Light Set

Bar with 2 derbies, 2 spots, white strobe LEDs, laser (RG, 2M), foot switch

Art. No.: 51741090

GTIN: 4026397532579



List price: 505.75 €

incl. 19% VAT.

Features:

- Crossbar with integrated DMX control unit and stand sleeve
 - 2 laser diodes project hundreds of red and green laser beams
 - 2 rotating derbies for mirror ball effects
 - For application areas such as: Wedding/gala/events; mobile use; Party room; mobile djs / entertainer; small rental
 - When fog is used, this effect becomes especially attractive
 - 37 integrated show programs
 - The device is cooled by cooling fan
 - Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Wireless footswitch; Master/slave function
 - With Mounting bracket
 - Preprogrammed in Light'J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
 - Mains input and output for power linking up to 8 units
 - Laser; multi beam effect; Strobe effect; flower effect
 - Application possibility: On stand
- laser**
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
2 spots controlled separately
 - With a beam angle of 13°
- light effect**
- 3 powerful LEDs 1 W high-power R/G/B
2 spots controlled separately
- bar**

Logistic

EAN / GTIN: 4026397532579

Weight: 11,00 kg

Length: 1.17 m

Width: 0.15 m

Height: 0.60 m

- 4 powerful LEDs 1 W high-power cold white (CW)
 LEDs controlled separately
- Package contents**
- 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x foot control, 1 x remote control, 2 x battery, 2 x mounting bracket, 2 x knurled screw, 1 x bag, 2 x washer

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Device fuse:	5 x 20 mm, F 1 A Fuse replaceable
Lamp type:	LED lamp
Flash rate:	0 - 30 Hz
DMX channels:	3; 5; 9; 27
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; Wireless footswitch; Master/slave function
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Housing color:	Black
Attachment system:	2x Mounting bracket
Dimensions:	Width: 1,09 m Depth: 14,5 cm Height: 37 cm
Weight:	9,05 kg
Noise classification:	Class 2 (slight noise)
Laser	
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
Spotlight	
LED:	3 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	20°
Light effect	
LED:	3 x 1 W high-power R/G/B
Bar	

LED:	4 x 1 W high-power cold white (CW)
Beam angle (1/2 peak):	7°
Foot control	
Battery:	1 x 9.0 V E block 6LR61 alkaline manganese included
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in