

## EUROLITE LED KLS Laser Bar FX Light Set

Bar with 2 derbies, 2 spots, white strobe LEDs, laser (RG, 2M), foot switch

Art. No.: 51741090

GTIN: 4026397532579



### Features:

- Crossbar with integrated DMX control unit and stand sleeve
- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- When fog is used, this effect becomes especially attractive
- Laser; multi beam effect; strobe effect; flower effect
- 37 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
- Fixtures available for Light' J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; mobile djs / entertainer; party room; restaurants, bars and hotels; wedding/gala/events
- Application possibility: On stand
- laser**
- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 LEDs 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)<BR>2 spots controlled separately
- With a beam angle of 13°
- light effect**
- 3 LEDs 1 W SMD 8072 R/G/B<BR>2 spots controlled separately

### Logistic

EAN / GTIN: 4026397532579

Weight: 11,00 kg

Length: 1.17 m

Width: 0.15 m

Height: 0.60 m

**bar**

- 4 LEDs 1 W SMD 8072 cold white (CW)<BR> LEDs controlled separately

## Technical specifications:

|                         |                                                                                                                |
|-------------------------|----------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                         |
| Power consumption:      | 50 W                                                                                                           |
| IP classification:      | IP20                                                                                                           |
| Protection class:       | Protection class I                                                                                             |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)               |
| Power output:           | 1 x IEC connector (F) mounting version                                                                         |
| Device fuse:            | 5 x 20 mm, F 1 A fuse replaceable                                                                              |
| Lamp type:              | LED lamp                                                                                                       |
| Flash rate:             | 0 - 30 Hz                                                                                                      |
| DMX channels:           | 3; 5; 9; 27                                                                                                    |
| DMX input:              | 1 x 3-pin XLR (M) mounting version                                                                             |
| DMX output:             | 1 x 3-pin XLR (F) mounting version                                                                             |
| Cooling:                | Cooling fan                                                                                                    |
| Control:                | Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function |
| Fixtures available for: | Light´ J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief                 |
| Housing color:          | Black                                                                                                          |
| Attachment system:      | Tube: 1x Ø 35mm<br>2x mounting bracket                                                                         |
| Display type:           | 4 digit 7-segment LED display                                                                                  |
| Dimensions:             | Width: 109 cm<br>Depth: 14.5 cm<br>Height: 37 cm                                                               |
| Weight:                 | 9.05 kg                                                                                                        |
| Noise classification:   | Class 2 (slight noise)                                                                                         |
| LED type:               | 3 x 1 W SMD 8072 R/G/B                                                                                         |
| LED type:               | 3 x 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)                                                           |
| Beam angle:             | 13°                                                                                                            |
| Beam angle (1/2 peak):  | 13°                                                                                                            |
| Beam angle (1/10 peak): | 20°                                                                                                            |
| Battery:                | 1 x 9.0 V E block 6LR61 alkaline manganese included                                                            |
| Battery:                | 1 x button cell 3.0 V CR2025 lithium manganese built-in                                                        |
| Laser class:            | 2M                                                                                                             |
| Laser color:            | R/G                                                                                                            |
| Laser module:           | Red (R) 100 mW 650nm<br>Green (G) 30 mW 532nm                                                                  |

|                        |                                  |
|------------------------|----------------------------------|
| LED type:              | 4 x 1 W SMD 8072 cold white (CW) |
| Beam angle (1/2 peak): | 7°                               |

### Scope of delivery:

---

1 x user manual  
1 x declaration of conformity  
1 x power cord  
1 x foot control  
1 x remote control  
2 x battery  
2 x mounting bracket  
2 x knurled screw  
1 x bag  
2 x washer