

EUROLITE LED KLS Laser Bar FX AIR

Art. No.: 51741099

Bar with 2 spots, 2 derbies, show laser, twinkle effect, AirW wireless system (2.4 GHz) and RF remote control

GTIN: 4026397740141



Features:

- Crossbar with integrated DMX control unit and stand sleeve
- Integrated AirW radio transceiver for wireless master/slave operation
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- When fog is used, this effect becomes especially attractive
- Dimmer electronic; color blend stepless; program selection; color change programs; color fade programs; running light programs; program speed adjustable
- Spot effect; laser; multi beam effect; strobe effect; twinkle effect
- Integrated show programs
- Direct color selection
- The device is cooled by cooling fan
- Control via stand-alone; DMX; AirW; sound to light via microphone; master/slave function; wireless remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); wireless footswitch (optional)
- Fixtures available for Light Captain; Colorchief
- Flicker-free
- AirW: operating range up to 70m
- DMX fail mode (blackout; hold; full on; auto)
- The article is delivered with practical transport bag
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels

Logistic

EAN / GTIN: 4026397740141
Weight: 9,20 kg
Length: 1.15 m
Width: 0.16 m
Height: 0.42 m

- Application possibility: Standing; suspended; on stand
- laser**
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 LEDs 8 W high-power 4in1 QCL RGB/WW (homogenous color mix)
2 spots controlled separately
- With a beam angle of 12°
- light effect**
- 4 LEDs 3 W high-power R/G/B/W
- 14 LEDs 0.2 W SMD 3535 3in1 TCL RGB (homogenous color mix)
2 spots controlled separately
- remote control**
- Operating range up to 30m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz AC
Power consumption:	65 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable construction:	3 x 1.0 mm ² H05VV-F
Cable length:	3 m
Power output:	1 x P-Con (gray), mounting version Bypass
Device fuse:	5 x 20 mm, T 1.6 A fuse replaceable
Fuse:	T 5 A fuse fix on board
Lamp type:	LED lamp
DMX channels:	3; 8; 11; 24; 27
DMX input:	1 x 3-pin XLR (M) mounting version 1 x USB, type A
DMX output:	1 x 3-pin XLR (F) mounting version Bypass
Cooling:	3 x cooling fan
Control:	Stand-alone; DMX; AirW; sound to light via microphone; master/slave function; wireless remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); wireless footswitch (optional)
Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
Range:	AirW: range up to 70m
Carrier frequency:	2.4 GHz
DMX fail mode:	Blackout; hold; full on; auto
Color temperature:	3100K; 5300K
Housing color:	Black matte
Attachment system:	Tube: Ø 35mm 2x mounting bracket
Display type:	Monochrome 4 digit 7-segment LED display

USB port:	1 x type A
Diameter mounting holes:	2 x Ø6mm
Use of brands:	Built with SEETRONIC connector
Material:	Metal, painted
Dimensions:	Length: 103 cm Depth: 8.2 cm Height: 33.6 cm
Weight:	8.10 kg
Noise classification:	Class 2 (slight noise)
Battery:	1 x 12 V 23AE alkaline manganese built-in
Range:	Range up to 30m
Carrier frequency:	433.92 MHz
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
LED type:	4 x 3 W high-power R/G/B/W 14 x 0.2 W SMD 3535 3in1 TCL RGB (homogenous color mix)
LED type:	3 x 8 W high-power 4in1 QCL RGB/WW (homogenous color mix)
Beam angle:	12°
Beam angle (1/2 peak):	Spot 12° multicolor
Beam angle (1/10 peak):	Spot 30°

Scope of delivery:

1 x device
 1 x power cord
 1 x user manual
 1 x declaration of conformity
 1 x remote control
 2 x knurled screw
 2 x mounting bracket
 2 x washer
 1 x bag
 1 x battery