# eurolite®

### **EUROLITE FBL-20 showlaser RGY**

High performance laser









## The article is no longer in our assortment.

#### Features:

- Laser with the classification 3B
- RGY-color-mixture
- Operation: MCU, DMX512, auto, sound-active
- Effects: layers, grids, tunnels, waves, writing, graphics, animation
- Laser diode: 650 nm red, 532 nm green
- Laser safety by key switch for locking startup and connection for emergency off
- EUROLITE NOT-01 Laser interlock (51741435) must be ordered separately in order to operate this laser!
- Read user manual before use. Laser installation, alignment and operation only by qualified and trained personell! Never open the housing!

#### **Technical specifications:**

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	30,00 W
Dimensions:	Width: 33,5 cm
	Depth: 27 cm
	Height: 13,5 cm
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
DMX channels:	9

#### Logistic

EAN / GTIN: 4026397353945 Weight: 6,00 kg Length: 0.40 m Width: 0.33 m Heigth: 0.25 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

DMX connection:	3-pin XLR
MCU-connection:	9-pin SUB-D
Maximum optical power:	20 mW
Laser classification:	3B
Wavelength:	650/532 nm
Laser-modules:	Red 20 mW, green 10 mW
Beam:	approx. 12 mm / 1 mrad
Scanning speed:	2000 pps
Dimensions without bracket (L x W x H):	335 x 270 x 135 mm
Weight:	5.5 kg