eurolite®

EUROLITE PSL-100 showlaser G

High performance laser











The article is no longer in our assortment.

Features:

- Laser with the classification 3B
- Operation: ILDA, DMX512, auto, sound-active
- Effects: layers, grids, tunnels, waves, writing, graphics, animation
- Laser diode: 532 nm green
- For DMX-operation on the rear panel: X and Y size adjustment
- Laser safety by integrated scan control, interlock with mechanic shutter, key switch for locking startup
- Read user manual before use. Laser installation, alignment and operation only by qualified and trained personell! Never open the housing!

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	40,00 W
Dimensions:	Width: 54 cm
	Depth: 33 cm
	Height: 24 cm
DMX channels:	11
DMX connection:	3-pin XLR
ILDA-connection:	25-pin SUB-D
Maximum optical power:	100 mW

Logistic

EAN / GTIN: 4026397353976 Weight: 14,75 kg Length: 0.60 m Width: 0.49 m Heigth: 0.35 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Laser classification:	3B
Wavelength:	532 nm
Beam:	approx. 4 mm / 1 mrad
Galvos:	max. ILDA 24K
Scanning speed:	30000 pps
Dimensions without bracket (L x W x H):	540 x 330 x 240 mm
Weight:	15 kg