eurolite®

EUROLITE VLS-700RGB 30k Showlaser

RGB laser with 700 mW

The article is no longer in our assortment.

Features:

- Laser with the classification 4
- Red, green, blue color-mixture
- Operation: ILDA, DMX512, auto, sound-active
- Effects: layers, grids, tunnels, waves, writing, graphics, animation
- For DMX-operation on the rear panel: X and Y size adjustment
- Laser safety by integrated scan control, interlock with mechanic shutter, key switch for locking startup
- Delivery in flightcase
- Control via stand-alone; DMX; ILDA

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	70,00 W
IP classification:	IP20
Laser class:	4
Laser color:	R/G/B
DMX channels:	13
Control:	Stand-alone; DMX; ILDA
Housing color:	Black
Dimensions:	Width: 51,5 cm

Logistic

EAN / GTIN: 4026397436334 Weight: 28,00 kg Length: 0.77 m Width: 0.46 m Heigth: 0.33 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Depth: 35 cm
	Height: 20,5 cm
Weight:	26,70 kg
DMX channels:	13
DMX connection:	3-pin XLR
ILDA connection:	25-pin SUB-D
Maximum optical power:	700 mW
Laser classification:	4
Wavelength:	650/532/445 nm
Laser modules:	Red 300 mW, green 100 mW, blue 300 mW
Beam:	5 mm @ output
Scanning speed:	30000 pps @ 8° ILDA
Beam divergence:	<1.8 mrad
Dimensions without bracket (L x W x H):	515 x 350 x 205 mm