eurolite®

EUROLITE VLS-1200RGB 20k Showlaser

RGB high-power laser











The article is no longer in our assortment.

Features:

- Laser with the classification 4
- Modulation: analog for more brilliant color changes
- Red, green, blue color-mixture
- Operation: ILDA, DMX512, auto, sound-active
- Effects: layers, grids, tunnels, waves, writing, graphics, animation
- For DMX-operation on the rear panel: X and Y size adjustment
- Laser safety by integrated scan control, interlock with mechanic shutter, key switch for locking startup
- Delivery in flightcase
- Read user manual before use. Laser installation, alignment and operation only by qualified and trained personell! Never open the housing!

Technical specifications:

70,00 W
Width: 51,5 cm
Depth: 35 cm
Height: 20,5 cm
27,65 kg
13
3-pin XLR

Logistic

EAN / GTIN: 4026397436327 Weight: 29,05 kg Length: 0.77 m Width: 0.46 m Heigth: 0.33 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

ILDA connection:	25-pin SUB-D
Maximum optical power:	1200 mW
Laser classification:	4
Wavelength:	650/532/445 nm
Laser modules:	Red 500 mW, green 300 mW, blue 400 mW
Beam:	5 mm @ output
Scanning speed:	20000 pps @ 8° ILDA
Beam divergence:	<1.8 mrad
Dimensions without bracket (L x W x H):	515 x 350 x 205 mm