

LASERWORLD CS-12.000RGB FX

Pure diode laser system

The article is no longer in our assortment.

Features:

- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; ILDA; sound to light via microphone
- 4 digit 7-segment LED display
- For further information about this product, please refer to the Data Sheet under "Downloads" Package contents
- 1 x laser, 1 x user manual, 1 x power cord, 1 x Interlock, 2 x key

Logistic

EAN / GTIN: 7640144997472 Weight: 8,90 kg Length: 0.45 m Width: 0.32 m Heigth: 0.25 m

Technical specifications:

| Power supply: | 100-240 V AC, 50/60 Hz |
|--------------------|--|
| Power consumption: | 200 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray) |
| Laser class: | 4 |
| Laser color: | R/G/B |
| Laser module: | Red (R) 2600 mW 638nm Green (G) 2900 mW 520nm |
| | |

| | Blue (B) 5500 mW 450nm |
|----------------|--|
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; master/slave function; ILDA; sound to light via microphone |
| Housing color: | Black |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Length: 28,5 cm |
| | Width: 18 cm |
| | Height: 19 cm |
| Weight: | 7,80 kg |
| | |