

# LASERWORLD CS-8000RGB FX MK2

Pure diode laser system



# The article is no longer in our assortment.

#### Features:

- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone; master/slave function; ILDA
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school
- Application possibility: Suspended Package contents
- 1 x laser, 1 x user manual, 1 x power cord, 1 x Interlock, 2 x key

### Logistic

EAN / GTIN: 7640144996024 Weight: 8,40 kg Length: 0.46 m Width: 0.32 m Heigth: 0.25 m

## **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	111 W
IP classification:	IP4X
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting versior power supply cord with safety plug
Power output:	1 x P-Con (gray), mounting version
Laser class:	4
Laser color:	R/G/B
Laser module:	Red (R) 1800 mW 638nm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Green (G) 1800 mW 520nm
	Blue (B) 3700 mW 450nm
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone; master/slave function; ILDA
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Length: 28,5 cm
	Width: 18,0 cm
	Height: 19,0 cm
Weight:	7,7 kg