

LASERWORLD DS-1000RGB MK4

Diode showlaser with ShowNET network interface and free software

Art. No.: 51743288

GTIN: 7640144997533



Features:

- Integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; ILDA; Art-Net; master/slave function
- For application areas such as: Clubs/dancing school; stage; wedding/gala/events; rental
- Application possibility: Suspended

Logistic

EAN / GTIN: 7640144997533

Weight: 4,75 kg

Length: 0.35 m

Width: 0.30 m

Height: 0.19 m

Technical specifications:

| | |
|--------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 40 W |
| IP classification: | IP4X |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x P-Con (gray), mounting version |
| Laser class: | 4 |
| Laser color: | R/G/B |
| Laser module: | Red (R) 200 mW 638nm Green (G) 250 mW 520nm Blue (B) 700 mW 450nm |

| | |
|----------------|--|
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; ILDA; Art-Net; master/slave function |
| Housing color: | Black |
| Dimensions: | Width: 14 cm Depth: 20 cm Height: 11 cm |
| Weight: | 4.00 kg |

Scope of delivery:

1 x laser
1 x user manual
1 x power cord
2 x key
1 x Interlock