

EUROLITE LED TMH-W63 Moving Head Zoom Wash

Washlight with 7 x 9 W LEDs, 4in1 QCL RGBW-Farbmischung and motorized zoom

Art. No.: 51785885

GTIN: 4026397672695



List price: 355.81 €

incl. 19% VAT.

Features:

- 7 powerful LEDs 9 W high-power 4in1 QCL RGBW (homogenous color mix)
- Positioning within 540° PAN and 220° TILT
- Exact positioning (16 bit resolution)
- Zoom motor-driven
- Motion macros adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 6° - 29°
- 4 digit 7-segment LED display
- Preprogrammed in Light J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Application possibility: Suspended; standing
- Rubber feet
- For application areas such as: Clubs/dancing school; Wedding/gala/events; mobile djs / entertainer; small rental

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet

Logistic

EAN / GTIN: 4026397672695

Weight: 4,75 kg

Length: 0.27 m

Width: 0.27 m

Height: 0.34 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 2 A Fuse replaceable
Lamp type:	LED lamp
LED:	7 x 9 W high-power 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	220° Exact positioning (16 bit resolution)
Max. PAN movement:	540° Exact positioning (16 bit resolution)
Equipment:	Zoom motor-driven
DMX channels:	15
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light'J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	6° - 29°
Beam angle (1/2 peak):	6 - 18°
Beam angle (1/10 peak):	11 - 29°
Illuminance in Lux (lx):	Narrow red (R) 1m: 7863 lx, 3m: 1074 lx, 6m: 269 lx Narrow green (G) 1m: 15691 lx, 3m: 2179 lx, 6m: 549 lx Narrow blue (B) 1m: 2497 lx, 3m: 406 lx, 6m: 103 lx Narrow cold white (CW) 1m: 17115 lx, 3m: 2398 lx, 6m: 605 lx Narrow all 1m: 40258 lx, 3m: 5714 lx, 6m: 1432 lx Wide red (R) 1m: 1586 lx, 3m: 187 lx, 6m: 49 lx Wide green (G) 1m: 3083 lx, 3m: 385 lx, 6m: 101 lx Wide blue (B) 1m: 568 lx, 3m: 73 lx, 6m: 20 lx Wide cold white (CW) 1m: 3372 lx, 3m: 407 lx, 6m: 106 lx Wide all 1m: 8103 lx, 3m: 994 lx, 6m: 257 lx
Housing color:	Black
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 21,0 cm Depth: 16,0 cm

	Height: 29,5 cm
Weight:	4,15 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting